

POSBANK®

Driving In-Store Performance

Contents

Driving In-Store Performance



INTRO

About Us
Company History
Capability

PRODUCTS

Kiosk	MAZIC K-2150 MAZIC K-1560 BIGPOS
POS	FORGED MAZIC APEXA CORE APEXA EDGE ACT
All in One POS	MINT
Panel PC	PTM PTC
KDS	KDS
Tablet	PAI TAB
Table Ordering	PAI
Box PC	MG BOX CR BOX
Monitor	POSMO
Printer	A series

BUSINESS

Embedded IoT
OEM·ODM
Global Network

About POSBANK

Based on customer centric engineering and unmatched industry knowledge, POSBANK offers a wide range of POS terminals, Kiosks, Touchscreen monitors, POS printer and related peripherals for hospitality and retail environments.

With continued focus on innovative POS terminals, Kiosks and custom solutions that meet specific needs of various global customers, our goal is to be the most trusted provider of solutions with best-in-class products and services.





Why POSBANK is Different?

We are committed to continuously improve our solutions and process through ongoing implementation of our five focus areas.

Innovation

We build innovative POS solutions that help customers to be more successful in their business.

Design

We deliver POS solutions with impressive design that enhance customers' brand image.

Quality

We strive to meet stringent standards fulfilled by our in-house R&D and manufacturing facility.

Continuity

We offer continued support for customers during the product life cycle.

Proximity

We operate global partner network and warehouses near customers' business.

POSBANK History



1994

- Establishment of Parent Company

1998

- POS Solution development of Food service

2000~2001

- Distribution of POS Solution
- ERP (SPEED ERP) Solution

2004

- POS System Business Agreement With KT (KT bizmeko)
- ASP (WEB) Solution

1994~2009

2006

- Small & Medium Business "INNO-BIZ" Certification
- A9 (POS Printer)

2007

- IMPREX (All-in-one POS)
- Slim POS

2008

- IMPREX Prime Good Design awarded
- Manufacturing Establishment in Bucheon, Gyeonggi-do
- Multi-lingual Restaurant POS Solution

2009

- Opening a logistics & repair center in Bucheon, Gyeonggi-do
- A10 (POS Printer)
- A10 Good Design awarded

2010

- mini0 (All-in-one POS)
- ISO9001 Certification

2011

- A7 (POS Printer)
- Any Shop Eco (POS)
- Selected as Hi Seoul Brand

2012

- Any Shop II (POS), A10 (POS printer)
- ISO14001 Certification
- Any Shop II Good Design awarded
- Trade Day : \$10 million Export Tower Winner

2016

- APEXA® G (POS)
- A11 (POS printer)
- APEXA® G Good Design awarded
- POPs Cloud (Cloud Web Service)
- ANYORDER™ (Mobile Order App)

2017

- DCR™ Red Dot Design awarded
- DCR™ Good Design awarded
- APEXA® PRIME, APEXA® GW (POS)
- DCR™X86, DCR™M4 (All-in-One POS)
- Selected as Global Small and Medium Enterprise by Small and Medium Business Administration

2018

- DCR™A1
- APEXA® A-1500, APEXA® AW-1950 (Android POS)
- Quqi (Android POS System)
- Tablet docking station Good Design awarded

2010~2019

2020~2025

2026 ~

2013

- Any Shop PRO (POS)
- Selected as Global Small and Medium Enterprise by Small and Medium Business Administration
- POPs Restaurant & POPs Retail POS Solution

2014

- Any Shop e2, BLUO (POS)
- Established a production plant in Guangzhou, China
- BOXPOS (PC POS), POSMO II (Touch Monitor)

2015

- IMPREX PRIME (All-in-one POS)
- ANYSHOP PRIME (POS)
- A7 (POS Printer)

2019

- APEXA® GW-1560, APEXA® AW-1560 series (POS)
- BIGPOS (Kiosk) Good Design awarded
- PANDORA (POS) Good Design awarded
- A8 (POS Printer)
- Trade Day : 30 Million Dollar Export Tower Winner

2020

- BIGPOS® 2150 (Kiosk)
- MAZIC GW-1560 (POS)
- MAZIC G-1500 (POS)

2021

- POSMO III (Monitors) 19.5
- BIGPOS® 1560 (Kiosk)

2022

- MAZIC K-2150, 1560
- ACT, APEXA Core, MAZIC(POS)
- Trade Day : 50 Million Dollar Export Tower Winner

2023

- Moved to New Factory(Pyeongtaek)

2024

- Listed on KOSDAQ in 2024
- KDS, PAI, EDGE

2025

- Establishment of a European corporation
- Investment and partnership for autonomous driving robots
- FORGED (POS)

2026

POSBANK Capability




Global leading manufacturer

POSBANK is a global leading manufacturer of POS/Kiosk hardware. With advanced engineering and unmatched experience, we manufacture and offer a wide range of POS terminals, Kiosks, Touchscreen monitors, POS printers, and related peripherals for hospitality and retail environments.



Total POS solution

POSBANK, a total POS solution company offers design, manufacturing, and servicing of all of our products in-house based on quality control based excellence.



Hardware Manufacturing

With in-house design, development, and manufacturing services with highest quality standards and components used, Voice of the Customer (VoC) are managed & tracked through our Smart Quality Management System resulting in highly reliable products.





The most reliable products

POSBANK offers OEM·ODM services with the most flexible customization to meet the needs of each customer. Offering in-depth expertise on design, tooling, sampling, manufacturing, and quality control.




Stringent quality control procedures

As an ISO9001 and ISO14001 certified company, we have stringent manufacturing and quality control procedures to ensure that our products reach our customers safely and as specified.

Smart QMS

POSBANK'S web-based SMART QUALITY MANAGEMENT SYSTEM allows various departments to monitor, manage, and implement necessary changes fast and efficiently, increasing overall product quality, internal processes, communications between related departments, and customer satisfaction.



This table lists various products with columns for item number, name, specification, and status. It includes a search bar and filters for '품목명' (Product Name) and '현황' (Status).

This table shows inspection results for aging tests, with columns for item number, name, specification, and inspection status. It includes a search bar and filters for '에이징 검사' (Aging Inspection).

This table displays outgoing inspection results, with columns for item number, name, specification, and inspection status. It includes a search bar and filters for '출마검사' (Outgoing Inspection).

MAZIC K-2150

MAZIC K-2150 has a compact and aesthetic design that can be installed on a table and used as a natural interior item. It is a kiosk that can be installed with a 21.5-inch display without compromising the aesthetics of the store and has excellent functionality.



MAZIC K-2150 Features



| Counter-Top



| Slim & Sleek



| OS Support



| Options

MAZIC K-2150 System

MAZIC® K-2150			
System			
	MAZIC K-2150 RL	MAZIC K-2150 AP	MAZIC K-2150 AN
Processors	Intel® Core™ 3 Processor 100U 10M Cache, up to 4.70 GHz Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N
Memory	8GB (DDR5 4800 MT/s, Max 96GB)	4GB (DDR4 3200 MT/s, Max 64GB)	4GB (DDR4 3200 MT/s, Max 32GB)
Storage	Form factor : NVMe M.2 2280-D2-M Mountable : 1 x NVMe M.2 2280 128GB		
Audio	HD Audio Codec		
RAID	RAID 0,1		Not supported
Operating Systems	Windows 10 IoT Enterprise LTSC : Version 21H1 or higher Windows 11 IoT Enterprise LTSC		
TPM	TPM 2.0		
	MAZIC K-2150 Q	MAZIC K-2150 A4	MAZIC K-2150 A2
Processors	QCS6490 Kryo670 1 x Gold @ 2.7GHz, 3 x Gold @ 2.4GHz, 4 x Silver @ 1.95GHz	RK3576 Quad Cortex-A72 @ 2.2 GHz Quad Cortex-A53 @ 2.0 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Memory	DDR4 6GB (Max 32GB)	DDR4 6GB (Max 16GB)	DDR4 4GB
Storage	UFS 128GB (Max 128GB)	eMMC 128GB (Max 128GB)	eMMC 32GB (Max 64GB)
Audio	HD Audio Codec		
RAID	Not supported		
Operating Systems	Android 13	Android 14 GMS	Android 9 / 12 GMS

MAZIC K-2150


Windows




Android



MAZIC K-2150 Display I Interface

21.5"



MAZIC® K-2150

Display	
Type	21.5" TFT LCD, LED Backlight
Resolution	1080 x 1920
Brightness	250 cd/m² (typ.)
Response	22 ms
Contrast Ratio	1000 CR (typ.)
Touchscreen	Projected Capacitive Touch

Interface	
USB	8 (2 x USB 3.0, 6 x USB 2.0)
Serial	3 (COM1~2, RJ-45, Full Signal, COM6, Tx/Rx Only, Reserved for SCR)
LAN	1 x Gigabit Ethernet (RJ-45)
WiFi/BT	MAZIC K-2150 RL / AP / AN : N/A MAZIC K-2150 Q / A4 : Wi-Fi 2.4G / 5G, BT 5.3 Combo MIMO MAZIC K-2150 A2 : Wi-Fi 2.4G / 5G, BT 5.0 Combo
Audio Port	N/A
Speaker	1 x 3W (Mono)

Power	
Power Supply	Adaptor 24V, 6.35A (DIN 3 Pin Jack)

Pedestal	
Material	Galvanized Steel Plate
Material Thickness	1.2T

MAZIC K-2150 Physical & Environmental

MAZIC® K-2150

Physical & Environmental

Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 60 °C at 10% to 90% Humidity
Dimensions (W x D x H)	System : 333 x 200 x 750 (mm), 13.11 x 7.87 x 29.53 (in) Pedestal : 333 x 200 x 892 (mm), 12.95 x 7.87 x 35.11 (in) Base plate : 440 x 310 x 8 (mm), 17.32 x 12.20 x 0.31 (in)
Packing Dimensions (W x D x H)	System : 820 x 280 x 420 (mm), 32.28 x 11.02 x 16.53 (in) Pedestal (with base plate) : 950 x 270 x 420 (mm), 37.4 x 10.62 x 16.53 (in)
Net Weight	System : 10,560g, 23.28 lbs Pedestal : 11,545g, 25.45 lbs Baseplate : 8,045g, 17.73 lbs
Packing Weight	System : 13,610g, 30.00 lbs Pedestal (with baseplate) : 23,580g, 51.98 lbs
Certification	CE, FCC, KC
Color	White / White+Dark Grey / Black

MAZIC K-2150 Options

MAZIC® K-2150

Options

Built-in Printer	3" Jam-Free Thermal Auto Cutter A8R Max. 250mm/s or A400 Max. 350mm/s Interface : Serial, USB
Barcode Scanner	1D, 2D
Camera	5M USB Interface (With Mic, Internal) (Factory Option)
Wi-Fi / BT	MAZIC K-2150 RL / AP / AN : M.2 for WiFi / BT MAZIC K-2150 Q / A4 / A2 : N/A
MSR	Comply with ISO 7811, Support 1 & 2 & 3 Track
Smart Card Reader	EMV Level 1
NFC Reader	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693
MDS	Supported
LED Light Bar	Supported
Wall Mounting (W x D x H)	280 x 214 x 200 (mm), 11.02 x 8.42 x 7.87 (in)
Custom Options	EFT Terminal Bracket, ADA Bracket, Universal Payment bracket

*Specifications may change without prior notice.

MAZIC K-1560

MAZIC K-1560 is a countertop kiosk equipped with dual side monitors. Store customers can self-service the 15.6-inch monitor or assist with payment at the store counter. This new concept compact kiosk will provide customers with a fresh shopping experience.



MAZIC K-1560 Features



| Dual screens



| Screen Tilting



| OS Support



| Screen orientation

MAZIC K-1560 System

MAZIC® K-1560			
System			
	MAZIC K-1560 RL	MAZIC K-1560 AP	MAZIC K-1560 AN
Processors	Intel® Core™ 3 Processor 100U 10M Cache, up to 4.70 GHz Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N
Memory	8GB (DDR5 4800 MT/s, Max 96GB)	4GB (DDR4 3200 MT/s, Max 64GB)	4GB (DDR4 3200 MT/s, Max 32GB)
Storage	Form factor : NVMe M.2 2280-D2-M Mountable : 1 x NVMe M.2 2280 128GB		
Audio	HD Audio Codec		
RAID	RAID 0,1		Not supported
Operating Systems	Windows 10 IoT Enterprise LTSC : Version 21H1 or higher Windows 11 IoT Enterprise LTSC		
TPM	TPM 2.0		
	MAZIC K-1560 Q	MAZIC K-1560 A4	MAZIC K-1560 A2
Processors	QCS6490 Kryo670 1 x Gold @ 2.7GHz, 3 x Gold @ 2.4GHz, 4 x Silver @ 1.95GHz	RK3576 Quad Cortex-A72 @ 2.2 GHz Quad Cortex-A53 @ 2.0 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Memory	DDR4 6GB (Max 32GB)	DDR4 6GB (Max 16GB)	DDR4 4GB
Storage	UFS 128GB (Max 128GB)	eMMC 128GB (Max 128GB)	eMMC 32GB (Max 64GB)
Audio	HD Audio Codec		
RAID	Not supported		
Operating Systems	Android 13	Android 14 GMS	Android 9 / 12 GMS

MAZIC K-1560


Windows




Android




MAZIC K-1560 Display I Interface

15.6"



15.6"



MAZIC® K-1560

Display

Type	15.6" TFT LCD, LED Backlight
Resolution	1080 x 1920, 1920x1080 (Dual Monitor)
Brightness	300 cd/m ² (typ.)
Response	25 ms
Contrast Ratio	1000 CR (Typical)
Touchscreen	Projected Capacitive Touch

Interface

USB	4 (2 x USB 3.0, 2 x USB 2.0)
Serial	2 (COM1~2, RJ-45, Full Signal)
LAN	1 x Gigabit Ethernet (RJ-45)
WiFi/BT	MAZIC K-1560 RL / AP / AN : N/A MAZIC K-1560 Q / A4 : Wi-Fi 2.4G/5G, BT 5.3 Combo MIMO MAZIC K-1560 A2 : Wi-Fi 2.4G/5G, BT 5.0 Combo
Audio Port	N/A
Speaker	1 x 5W (Mono), 2 x 5W (Stereo) (Factory Option)

Power

Power Supply	Adaptor 24V, 6.35A (DIN 3 Pin Jack)
--------------	-------------------------------------

Pedestal

Material	HGI
Material Thickness	3mm

MAZIC K-1560 Physical & Environmental

MAZIC® K-1560

Physical & Environmental

Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 60 °C at 10% to 90% Humidity
Dimensions (W x D x H)	350 x 239 x 602 (mm), 13.78 x 10.98 x 23.7 (in)
Packing Dimensions (W x D x H)	389 x 316 x 638 (mm), 15.31 x 12.44 x 25.12 (in)
Net Weight	11,080g, 24.42 lbs
Packing Weight	Single Monitor : 11,560g, 25.49 lbs Dual Monitor : 14,000g, 30.86 lbs
Certification	CE, FCC, KC
Color	Black / White

MAZIC K-1560 Options

MAZIC® K-1560

Options

Built-in Printer	3" Jam-Free Thermal Auto Cutter A8R Max. 250mm/s or A400 Max. 350mm/s Interface : Serial, USB
Barcode Scanner	1D / 2D
Camera	5M USB Interface (With Mic, Internal) (Factory Option)
Wi-Fi / BT	MAZIC K-2150 RL / AP / AN : M.2 for WiFi/BT MAZIC K-2150 Q / A4 / A2 : N/A
MSR	Comply with ISO 7811, Support 1 & 2 & 3 Track
Smart Card Reader	EMV Level 1
NFC Reader	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693
MDS	Supported
LED Light Bar	Supported
Wall Mounting (W x D x H)	280 x 214 x 200 (mm), 11.02 x 8.42 x 7.87 (in)
Custom Options	EFT Terminal Bracket, ADA Bracket, Universal Payment bracket

*Specifications may change without prior notice.

BIGPOS®

BIGPOS® is a whole new self-service kiosk for retail stores and quick-service restaurants. It delivers an elegant look, easy installation, and quick maintenance.



BIGPOS® Features



Compact slim



Flexible installation
(Floor / Wall / Table)



Options
(Scanner, MSR / SCR, NFC etc.)



OS Support

BIGPOS® System

	BIGPOS® RL	BIGPOS® AP	BIGPOS® AN	BIGPOS® A2
System				
	Windows			Android
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-1335U Processor 12M Cache, up to 4.60 GHz	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N	-
Memory	4GB (DDR4 3200 MT/s, Max 96GB)	4GB (DDR4 3200 MT/s, Max 32GB)	4GB (DDR4 3200 MT/s, Max 16GB)	4GB Standard, LPDDR4, On-board
Storage	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI			eMMC 32GB, On-board (Max.64GB)
Audio	HD Audio Codec			
Raid	Raid 0, 1		Not Supported	
Operating Systems	Windows 10 version 21H1 / Windows 11 version 24H2			Android 9 / 12
TPM	TPM 2.0			N/A

BIGPOS®



Superior performance



Powerful performance



Efficient performance

BIGPOS® Display

27"



21.5"




	BIGPOS® RL	BIGPOS® AP	BIGPOS® AN	BIGPOS® A2
Display				
	BIGPOS® RL-2700	BIGPOS® AP-2700	BIGPOS® AN-2700	BIGPOS® A2-2700
Type	27" TFT LCD, LED Backlight			
Resolution	1080 x 1920			
Brightness	300 cd/m ² (typ.)			
Response	12 ms			
Contrast Ratio	3000 (typ.)			
Touchscreen	Projected Capacitive Touch			
	BIGPOS® RL-2150	BIGPOS® AP-2150	BIGPOS® AN-2150	BIGPOS® A2-2150
Type	21.5" TFT LCD, LED Backlight			
Resolution	1080 x 1920			
Brightness	250 cd/m ² (typ.)			
Response	22 ms			
Contrast Ratio	1000 (typ.)			
Touchscreen	Projected Capacitive Touch			

BIGPOS® Interface

	BIGPOS® RL	BIGPOS® AP	BIGPOS® AN	BIGPOS® A2
Interface				
USB	2 x USB 2.0			
Serial	2 (COM2~3, RJ-45, Full Signal)			
LAN	1 x Gigabit Ethernet (RJ-45)			
Wi-Fi / BT	N/A			Wi-Fi 2.4G/5G (802.11 a/b/g/n, 2.4G/5G), BT 5.0 Combo (FactoryOption)
Audio Port	N/A			
Speaker	1 x 5W (Mono), 2 x 5W (Stereo) (Factory Option)			
Power				
Power Supply	Adaptor 24V, 6.35A (DIN 3 Pin Jack)			
Pedestal				
Material	Galvanized Steel Plate			
Material Thickness	1.2T			
Component Access	BIGPOS RL / AP / AN /A2 2700 : Security Locks with 7-Pin Tumbler / Rear Security Door BIGPOS RL / AP / AN /A2 2150 : N/A			

BIGPOS® I/O Ports




BIGPOS® Physical & Environmental

	BIGPOS® RL	BIGPOS® AP	BIGPOS® AN	BIGPOS® A2
--	------------	------------	------------	------------

Physical & Environmental

Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity			
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity			
	BIGPOS® RL-2700	BIGPOS® AP-2700	BIGPOS® AN-2700	BIGPOS® A2-2700
Dimensions (W x D x H)	System : 426 x 135 x 880 (mm), 16.7 x 5.3 x 34.6 (in) Pedestal: 426 x 135 x 870 (mm), 16.7 x 5.3 x 34.2 (in) Base plate : 600 x 450 x 10 (mm), 23.6 x 17.7 x 0.4 (in) Base plate (Counter Top) : 466 x 295 x 6 (mm), 18.3 x 11.6 x 0.2 (in)			
Packing Dimensions (W x D x H)	System : 515 x 265 x 980 (mm), 20.2 x 10.4 x 38.5 (in) Pedestal : 515 x 265 x 980 (mm), 20.2 x 10.4 x 38.5 (in) Base plate : 770 x 550 x 65 (mm), 30.3 x 21.6 x 2.5 (in)			
Net Weight	System : 15,000g, 33.06 lbs Pedestal : 13,000g, 28.66 lbs Base plate : 20,000g, 44.09 lbs			
Packing Weight	System : 21,000g, 46.29 lbs Pedestal : 17,000g, 37.47 lbs Base plate : 21,000g, 46.29 lbs			
Certification	CE, FCC, KC			
Color	High Gloss White / High Gloss Black / Custom Colors Available			
	BIGPOS® RL-2150	BIGPOS® AP-2150	BIGPOS® AN-2150	BIGPOS® A2-2150
Dimensions (W x D x H)	System : 360 x 120 x 760 (mm), 14.1 x 4.7 x 30.0 (in) Pedestal : 360 x 120 x 890 (mm), 14.1 x 4.7 x 35.0 (in) Base plate : 440 x 310 x 8 (mm), 17.3 x 12.2 x 0.3 (in) Base plate (Counter Top) : 400 x 280 x 6 (mm), 15.7 x 11.0 x 0.2 (in)			
Packing Dimensions (W x D x H)	System: 500 x 240 x 880 (mm), 19.7 x 9.4 x 34.6 (in) Pedestal: 500 x 240 x 1000 (mm), 19.7 x 9.4 x 39.3 (in)			
Net Weight	System : 15,000g, 33.06 lbs Pedestal : 9,000g, 19.84 lbs Base plate : 7,000g, 15.43 lbs			
Packing Weight	System : 13,900g, 30.64 lbs Pedestal (with Baseplate) : 19,300g, 42.55 lbs			
Certification	CE, FCC, KC			
Color	High Gloss White, High Gloss Black, Custom Colors Available			

BIGPOS® Option



	BIGPOS® RL	BIGPOS® AP	BIGPOS® AN	BIGPOS® A2
Options				
Storage	2.5 inch SSD 128GB, HDD 500GB, 1TB M.2 2242-D2-M (SATA or NVMe)			N/A
Built-in Printer	3" Jam-Free Thermal, Max. 250mm/s, Auto Cutter, Interface : Serial, USB			
Barcode Scanner	1D / 2D			
Camera	1 x 5M Pixel (Internal USB Interface)			
Wi-Fi / BT	M.2 for WiFi/BT			N/A
MSR	Comply with ISO 7811, Support 1/2/3 Track			
Smart Card Reader	EMV Level 1			
NFC Reader	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693			
Key Reader	Supported, Dallas i-Button Reader			
Fingerprint Reader	Supported			
LED Light Bar	Supported			
Wall Mounting	VESA, 100 x 100 (mm), 200 x 200 (mm)			
Custom Options	EFT Terminal Bracket option, Customer-Assigned EMV Terminal Bracket, Bill/Coin Acceptor, Document Reader (Passports/IDs), Ticket/Document Printer, UPS (Uninterruptible Power Supply)			


*Specifications may change without prior notice.

FORGED


FORGED is a premium POS equipped with 15.6" and 15" displays and a 13th Gen Intel CPU. Combining sleek design with robust performance, it is optimized for retail environments and ideal for high-end store operations.



FORGED Features



Expandable I/O



Fanless cooling system



High performance



Cable-Free connection

FORGED System

	FORGED RL	FORGED AN
System		
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-13355U Processor 12M Cache, up to 4.60 GHz"	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-N
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max 96GB)	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max 16GB)
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 2 x NVMe M.2 2242, Default : 1 x 128GB	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Default : 1 x 128GB
Audio	HD Audio Codec	
RAID	RAID 0,1	
Operating Systems	Windows 10 IoT Enterprise LTSC : Version 21H1 or higher Windows 11 IoT Enterprise LTSC	
TPM	TPM 2.0	

FORGED




Superior performance




Powerful performance

FORGED Display | Interface

15.6"



15"



	FORGED RL	FORGED AN
Display		
	FORGED RL-1560	FORGED AN-1560
Type	15.6" FHD TFT LCD, LED Backlight	
Resolution	1920 x 1080	
Brightness	300 cd/m² (Typ.)	
Response	25 ms	
Contrast Ratio	1000 (Typ.)	
Touchscreen	Projected Capacitive Touch, AF	
	FORGED RL-1500	FORGED AN-1500
Type	15" TFT LCD, LED Backlight	
Resolution	1024 x 768	
Brightness	400 cd/m²	
Response	25 ms	
Contrast Ratio	1000 (Typ.)	
Touchscreen	Projected Capacitive Touch, AF	
	FORGED RL	FORGED AN
Interface		
Display	2 (1 x HDMI, 1 x USB Type-C (Alt-Mode))	
USB	7 (1 x USB 2.0 3 x USB 3.0 1 x USB Type-C 1 x 24V Powered USB 1 x 12V Powered USB) * 12V/24V Powered USB can be changed to USB 2.0 depending on customer needs.	
Serial	3 (COM1~3, RJ45, Full Signal)	
LAN	1 x Gigabit Ethernet (RJ-45)	
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)	
Audio Port	1 x Line out	
Speaker	1 x 3W (Mono) (Factory Option)	
Power		
Power Supply	Adaptor 24V/6.35A (DIN 3 Pin Jack) Adaptor 24V/11A (DC 2.5Ø Jack) (Stand I/O Option)	

FORGED Physical & Environmental | Options & Peripherals

	FORGED RL		FORGED AN	
Physical & Environmental				
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity			
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity			
IP Grade	IP54			
	FORGED RL-1560		FORGED AN-1560	
Dimensions (WxDxH)	365 x 211 x 281 (mm), 14.4 x 8.3 x 11.1 (in)			
Packing Dimensions (W x D x H)	455 x 308 x 163 (mm), 17.9 x 12.1 x 6.42 (in)			
Net Weight	3,300g, 7.28 lbs			
Packing Weight	5,400g, 11.9 lbs			
	FORGED RL-1500		FORGED AN-1500	
Dimensions (WxDxH)	325 x 211 x 294 (mm), 12.8 x 8.3 x 11.5 (in)			
Packing Dimensions (W x D x H)	455 x 308 x 163 (mm), 17.9 x 12.1 x 6.42 (in)			
Net Weight	3,600g, 7.94 lbs			
Packing Weight	5,700g, 12.6 lbs			
	FORGED RL		FORGED AN	
Certification	CE, FCC, KC, CB			
Construction	Aluminum Die-Casting, Plastic			
Color	Titanium grey / Black / White			
Options & Peripherals				
Optional Display	- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)			
Optional I/O Box	Stand I/O USB 3 (1 x USB Type-C 1 x 24V Powered USB 1 x 12V Powered USB * USB Type-C for communication only (Not a memory connector) * 12V/24V Powered USB can be changed to USB 2.0 depending on customer needs. Stand I/O Serial 2 (2 x COM, RJ45, Full Signal)			
Storage	M.2 2242 128GB (NVMe)			
Wi-Fi / BT	M.2 for Wi-Fi6 / BT 5.2			
MSR	Comply with ISO 7811, Support 1/2/3 Track			
Smart Card Reader	EMV Level 1			
NFC Reader	TBD			
Key Reader	Supported, Dallas i-Button Reader			
Fingerprint Reader	Supported			
Wall Mounting	VESA, 75 x 75 (mm), 100 x 100 (mm)			
Serial Conversion Cable	RJ-45 to D-sub 9			

*Specifications may change without prior notice.

MAZIC® Prime

MAZIC PRIME is a POS that actively reflects the needs of high-end customers with an upgraded heat sink and a thinner design than the existing high-end MAZIC.




MAZIC® Prime Features




Efficient use of heat sink



Foldable, Dual hinges



High performance



Ultra thin bezel

MAZIC® Prime System

	MAZIC® PRIME RL	MAZIC® PRIME AP	MAZIC® PRIME AN
System			
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-1335U Processor 12M Cache, up to 4.60 GHz"	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz"	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 32GB)		4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 2 x NVMe M.2 2242, Default : 1 x 128GB		
Audio	HD Audio Codec		
RAID	RAID 0,1		Not Supported
Operating Systems	Windows 10/11 version 21H1 or higher		
TPM	TPM 2.0		

MAZIC® Prime




Superior performance



Powerful performance

MAZIC® Prime Display | Interface

15.6"



15"



	MAZIC® PRIME RL	MAZIC® PRIME AP	MAZIC® PRIME AN
Display			
	MAZIC PRIME RL-1560	MAZIC PRIME AP-1560	MAZIC PRIME AN-1560
Type	15.6" TFT LCD, LED Backlight		
Resolution	1920 x 1080		
Brightness	300 cd/m² (Typ.)		
Touchscreen	Projected Capacitive Touch, AF		
	MAZIC PRIME RL-1500	MAZIC PRIME AP-1500	MAZIC PRIME AN-1500
Type	15" TFT LCD, LED Backlight		
Resolution	1024 x 768		
Brightness	400 cd/m² (typ.)		
Touchscreen	Projected Capacitive Touch, AF		
	MAZIC® PRIME RL	MAZIC® PRIME AP	MAZIC® PRIME AN
Interface			
Display	1 x Displayport (mDP)		
USB	Option 1 : 7 (2 x USB 3.0, 4 x USB 2.0, 1 x USB C-type) Option 2 : 5 (4 x USB 2.0, 1 x USB C-type)		
Serial	Option 1 : 2 (COM3~4, RJ-45, Full Signal) Option 2 : 3 (COM3~5, RJ-45, Full Signal)		
LAN	1 x Gigabit Ethernet (RJ-45)		
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)		
Audio Port	1 x Line-out(Stereo)		
Speaker	1 x 1W (Mono)		
Power			
Power Supply	Adaptor 12V, 5A (USB Type-C Plug)		

MAZIC® Prime Physical & Environmental | Options & Peripherals

	MAZIC® PRIME RL		MAZIC® PRIME AP		MAZIC® PRIME AN	
Physical & Environmental						
Operating Temperature		0 °C ~ 60 °C at 10% to 90% Humidity				
Storage Temperature		-20 °C ~ 80 °C at 10% to 90% Humidity				
	MAZIC PRIME RL-1560		MAZIC PRIME AP-1560		MAZIC PRIME AN-1560	
Dimensions (WxDxH)		368 x 230 x 395 (mm), 14.5 x 9.0 x 15.5 (in)				
Packing Dimensions (W x D x H)		485 x 150 x 325 (mm), 19 x 5.9 x 12.7 (in)				
Net Weight		5,500g, 12.13 lbs				
Packing Weight		6,000g, 13.23 lbs				
	MAZIC PRIME RL-1500		MAZIC PRIME AP-1500		MAZIC PRIME AN-1500	
Dimensions (WxDxH)		329 x 230 x 428 (mm), 12.9 x 9 x 16.8 (in)				
Packing Dimensions (W x D x H)		454 x 164 x 405 (mm), 17.8 x 15.9 x 6.5 (in)				
Net Weight		4,900kg, 10.8 lbs				
Packing Weight		5,400kg, 11.9 lbs				
	MAZIC® PRIME RL		MAZIC® PRIME AP		MAZIC® PRIME AN	
Certification		CE, FCC, KC				
Color		Black/White				
Options & Peripherals						
2nd Displays		- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)				
Customer Display		2 x USB 2.0 (Factory Option) - Option 1 : 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) - Option 2 : 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 3 : 1 x 12V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 4 : 6 x USB 2.0 / 2 x RJ45 (Full Signal)				
Storage		M.2 2242 128GB (NVMe)				
Wi-Fi / BT		Combo module Wi-Fi / BT (SMT, Factory option)				
MSR		Comply with ISO 7811, Support 1/2/3 Track				
Smart Card Reader		EMV Level 1				
Key Reader		Supported, Dallas i-Button Reader				
Fingerprint Reader		Supported				
Wall Mounting		VESA, 75 x 75 (mm), 100 x 100 (mm)				
Serial Conversion Cable		RJ-45 to D-sub 9 for Interface Option 2, 3				

*Specifications may change without prior notice.

MAZIC®

Introducing the all-new high-end MAZIC® that entirely refined point of sale system, MAZIC® adapts simplified and modernized design.



MAZIC® Features




| Fast and easy maintenance



| Foldable, Dual hinges



| High performance



| Ultra thin bezel

MAZIC® System

	MAZIC® RL	MAZIC® AP	MAZIC® AN
System			
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-1335U Processor 12M Cache, up to 4.60 GHz"	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz"	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N
Memory	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 32GB)		4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 16GB)
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 2 x NVMe M.2 2242, Default : 1 x 128GB		
Audio	HD Audio Codec		
RAID	RAID 0,1		Not Supported
Operating Systems	Windows 10 LTSC Windows 11 LTSC Ver. 24H2 or higher		
TPM	TPM 2.0		

MAZIC®




Superior performance




Powerful performance

MAZIC® Display | Interface

15.6"



15"



	MAZIC® RL	MAZIC® AP	MAZIC® AN
Display			
	MAZIC® RL-1560	MAZIC® AP-1560	MAZIC® AN-1560
Type	15.6" TFT LCD, LED Backlight		
Resolution	1920 x 1080		
Brightness	300 cd/m ² (Typ.)		
Touchscreen	Projected Capacitive Touch, AF		
	MAZIC® RL-1500	MAZIC® AP-1500	MAZIC® AN-1500
Type	15" TFT LCD, LED Backlight		
Resolution	1024 x 768		
Brightness	400 cd/m ² (Typ.)		
Touchscreen	Projected Capacitive Touch, AF		
	MAZIC® RL	MAZIC® AP	MAZIC® AN
Interface			
Display	1 x miniDP, 1 x USB Type-C (Alt-mode)		
USB	Option 1 : 7 (2 x USB 3.0, 4 x USB 2.0, 1 x USB C-type) Option 2 : 5 (4 x USB 2.0, 1 x USB C-type)		
Serial	Option 1 : 2 (COM3~4, RJ-45, Full Signal) Option 2 : 3 (COM3~5, RJ-45, Full Signal)		
LAN	1 x Gigabit Ethernet (RJ-45)		
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)		
Audio Port	1 x Line out		
Speaker	1 x 1W (Mono)		
Power			
Power Supply	Adapter 12V, 5A (USB-C Type Plug)		

MAZIC® Physical & Environmental | Options & Peripherals

	MAZIC® RL	MAZIC® AP	MAZIC® AN
Physical & Environmental			
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity		
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity		
	MAZIC® RL-1560	MAZIC® AP-1560	MAZIC® AN-1560
Dimensions (W x D x H)	368 x 230 x 395 (mm), 14.5 x 9.0 x 15.5 (in)		
Packing Dimensions (W x D x H)	485 x 150 x 325 (mm), 19.1 x 5.9 x 12.7 (in)		
Net Weight	5,000g, 12.02 lbs		
Packing Weight	5,500g, 12.13 lbs		
	MAZIC® RL-1500	MAZIC® AP-1500	MAZIC® AN-1500
Dimensions (WxDxH)	329 x 230 x 428 (mm), 12.9 x 9.0 x 16.8 (in)		
Packing Dimensions (W x D x H)	454 x 64 x 405 (mm), 17.8 x 6.5 x 15.9 (in)		
Net Weight	4,500g, 9.92 lbs		
Packing Weight	5,000g, 11.02 lbs		
	MAZIC® RL	MAZIC® AP	MAZIC® AN
Certification	CE, FCC, KC		
Color	Black / White		
Options & Peripherals			
Optional Display	- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)		
Optional I/O Box	2 x USB 2.0 (Factory Option) - Option 1 : 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) - Option 2 : 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 3 : 1 x 12V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 4 : 6 x USB 2.0 / 2 x RJ45 (Full Signal) * One option attached at a time		
Storage	M.2 2242 128GB (NVMe)		
Wi-Fi / BT	Combo module Wi-Fi / BT (SMT, Factory option)		
MSR	Comply with ISO 7811, Support 1/2/3 Track		
Smart Card Reader	EMV Level 1		
Key Reader	Supported, Dallas i-Button Reader		
Fingerprint Reader	Supported		
Wall Mounting	VESA, 75 x 75 (mm), 100 x 100 (mm)		
Serial Conversion Cable	RJ-45 to D-sub 9 for Interface Option 2, 3		
Speaker	1 x 1W (MONO)		

*Specifications may change without prior notice.

MAZIC® CX

MAZIC CX is a POS system optimized for customers in the restaurant and retail industries using the LCM module compared to the MAZIC.



MAZIC® CX Features




LCM modules to reduce TCO



Foldable, Dual hinges



High performance



Ultra thin bezel

MAZIC® CX System

MAZIC® CX	
System	
Processors	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Alder Lake-N
Memory	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 16GB)
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 2 x NVMe M.2 2242, Default : 1 x 128GB
Audio	HD Audio Codec
RAID	Not Supported
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher
TPM	TPM 2.0


MAZIC® CX




Powerful performance

MAZIC® CX Display | Interface

15.6"



15"



MAZIC® CX

Display

	MAZIC® CX-1560
Type	15.6" TFT LCD, LED Backlight
Resolution	1920 x 1080
Brightness	350 cd/m ² (Typ.)
Touchscreen	Projected Capacitive Touch, AF
	MAZIC® CX-1500
Type	15" TFT LCD, LED Backlight
Resolution	1024 x 768
Brightness	400 cd/m ² (Typ.)
Touchscreen	Projected Capacitive Touch, AF

MAZIC® CX

Interface

Display	1 x miniDP
USB	Option 1 : 9 (2 x USB 3.0, 6 x USB 2.0, 1 x USB C-type) Option 2 : 7 (2 x USB 3.0, 4 x USB 2.0, 1 x USB C-type) Option 3 : 5 (4 x USB 2.0, 1 x USB C-type)
Serial	Option 1 : 1 (COM3, RJ-45 , Full Signal) Option 2 : 2 (COM3~4, RJ-45, Full Signal) Option 3 : 3 (COM3~5, RJ-45, Full Signal)
LAN	1 x Gigabit Ethernet (RJ-45)
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)
Audio Port	1 x Line out
Speaker	1 x 1W (Mono)

Power

Power Supply	Adapter 12V, 5A (USB-C Type Plug)
--------------	-----------------------------------

MAZIC® CX Physical & Environmental | Options & Peripherals

MAZIC® CX

Physical & Environmental

Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
MAZIC® CX-1560	
Dimensions (W x D x H)	368 x 230 x 395 (mm), 14.5 x 9.0 x 15.5 (in)
Packing Dimensions (W x D x H)	485 x 150 x 325 (mm), 19.1 x 5.9 x 12.7 (in)
Net Weight	5,000g, 12.02 lbs
Packing Weight	5,500g, 12.13 lbs
MAZIC® CX-1500	
Dimensions (W x D x H)	329 x 230 x 428 (mm), 12.9 x 9.0 x 16.8 (in)
Packing Dimensions (W x D x H)	454 x 64 x 405 (mm), 17.8 x 6.5 x 15.9 (in)
Net Weight	4,500g, 9.92 lbs
Packing Weight	5,000g, 11.02 lbs

MAZIC® CX

Certification	CE, FCC, KC
Color	Black / White

Options & Peripherals

Optional Display	- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)
Optional I/O Box	2 x USB 2.0 (Factory Option) - Option 1 : 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) - Option 2 : 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 3 : 1 x 12V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 4 : 6 x USB 2.0 / 2 x RJ45 (Full Signal)
Storage	M.2 2242 128GB (NVMe)
Wi-Fi / BT	Combo module Wi-Fi / BT (SMT, Factory option)
MSR	Comply with ISO 7811, Support 1/2/3 Track
Smart Card Reader	EMV Level 1
Key Reader	Supported, Dallas i-Button Reader
Fingerprint Reader	Supported
Wall Mounting	VESA, 75 x 75 (mm), 100 x 100 (mm)
Serial Conversion Cable	RJ-45 to D-sub 9 for Interface Option 2, 3

*Specifications may change without prior notice.

APEXA® CORE

APEXA® CORE is the next generation of APEXA®. With its sophisticated sense in a modern and contemporary style, APEXA® CORE offers fast and easy access and convenient upgrades with plenty of I/O ports to accommodate many options.



APEXA® CORE Features



Ultra thin bezel



High performance



Fast and easy maintenance



External I/O box


APEXA® CORE System

	APEXA CORE RL	APEXA CORE AP	APEXA CORE AN
System			
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-1335U Processor 12M Cache, up to 4.60 GHz"	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz"	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 32GB)		4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)
Storage	1. Form Factor NVMe M.2 2242-D2-M (No capacity limit.) 2. Mountable quantity: Up to 2 units can be installed. * Factory Default : NVMe M.2 2242 128GB x 1		
Audio	HD Audio Codec		
RAID	RAID 0,1		Not Supported
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher		
TPM	TPM 2.0		

APEXA® CORE



Superior performance



Powerful performance

APEXA® CORE Display

15.6"



15"



	APEXA CORE RL	APEXA CORE AP	APEXA CORE AN
Display			
	APEXA CORE RL-1560	APEXA CORE AP-1560	APEXA CORE AN-1560
Type	15.6" FHD TFT LCD, LED Backlight		
Resolution	1920 x 1080		
Brightness	300 cd/m ² (typ.)		
Touchscreen	Projected Capacitive Touch, AF		
	APEXA CORE RL-1500	APEXA CORE AP-1500	APEXA CORE AN-1500
Type	15" TFT LCD, LED Backlight		
Resolution	1024 x 768		
Brightness	350 cd/m ² (typ.)		
Touchscreen	Projected Capacitive Touch, AF		

APEXA® CORE Interface

	APEXA CORE RL	APEXA CORE AP	APEXA CORE AN
Interface			
Display	2 (1 x miniDP, 1 x USB Type-C (Alt-Mode))		
USB	8 (2 x USB 3.0, 5 x USB 2.0, 1 x USB Type-C)		
Serial	4 (COM1, RJ45 with 5V/12V Power Output on 6 Pins, BIOS COM2~3, RJ-45, Full Signal COM5, Full Signal)		
LAN	1 x Gigabit Ethernet (RJ-45)		
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)		
Audio Port	1 x Line out		
Speaker	1 x 1W (Mono)		
Power			
Power Supply	- 12V, 5A (Normal) - 24V, 6.35A (EXT I/O BOX Option)		

APEXA® CORE I/O Ports

REAR

① AUDIO ② USB ③ LAN ④ DC IN ⑤ COM3 ⑥ COM2 ⑦ USB-C ⑧ USB ⑨ POWER SW
⑩ USB ⑪ miniDP ⑫ COM1

FRONT

⑬ Cash Drawer ⑭ 4 x USB ⑮ COM5

DCIN Voltage		+24V	+12V
USB	USB 2.0	x 4	x 4
	+24V Powered USB	x 1	NO
	+12V Powered USB	x 1	NO
Serial	RJ45	NO	x 1
CashDrawer	RJ12	NO	x 1

APEXA® CORE Physical & Environmental

	APEXA CORE RL	APEXA CORE AP	APEXA CORE AN
Physical & Environmental			
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity		
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity		
	APEXA CORE RL-1560	APEXA CORE AP-1560	APEXA CORE AN-1560
Dimensions (W x D x H)	372 x 230 x 303 (mm), 14.6 x 9.0 x 11.9 (in)		
Packing Dimensions (W x D x H)	435 x 165 x 485 (mm), 17.1 x 6.5 x 19.1 (in)		
Net Weight	3,400g, 7.5 lbs		
Packing Weight	4,500g, 9.9 lbs		
	APEXA CORE RL-1500	APEXA CORE AP-1500	APEXA CORE AN-1500
Dimensions (W x D x H)	351 x 206 x 308 (mm), 13.8 x 8.11 x 13.8 (in)		
Packing Dimensions (W x D x H)	435 x 165 x 485 (mm), 17.1 x 6.5 x 19.1 (in)		
Net Weight	4,410g, 9.7 lbs		
Packing Weight	5,500g, 12.1 lbs		
	APEXA CORE RL	APEXA CORE AP	APEXA CORE AN
Certification	CE, FCC, KC		
Color	Dark Grey / White		

APEXA® CORE Options & Peripherals

	APEXA CORE RL	APEXA CORE AP	APEXA CORE AN
Options & Peripherals			
Optional Display	- 2nd Display (9.7" (1024 x 768) - 2nd Display (10.1" (1280 x 800) - 2nd Display (15" (1024 x 768) - 2nd Display (15.6" (1920 x 1080) - VFD (2 Lines x 20 Columns)		
Optional I/O Box	- USB 2.0 x 2 (Factory option) - Option 1 : 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) - Option 2 : 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 3 : 1 x 12V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 4 : 6 x USB 2.0 / 2 x RJ45 (Full Signal) *One option attachable at a time		
Storage	M.2 2242 128GB (NVMe)		
Wi-Fi / BT	Combo module Wi-Fi / BT (SMT, Factory option)		
MSR	Comply with ISO 7811, Support 1/2/3 Track		
Smart Card Reader	EMV Level 1		
Key Reader	Supported, Dallas i-Button Reader		
Fingerprint Reader	Supported		
Wall Mounting	VESA, 75 x 75 (mm), 100 x 100 (mm)		
Serial Conversion Cable	RJ-45 to D-sub 9 for Interface Option 2, 3		

*Specifications may change without prior notice.

APEXA® CX

APEXA CX has improved economic efficiency and convenience by applying SATA SSD to APEXA CORE's compact 15-inch display. It applies 12th generation CPU to realize excellent performance of the system in restaurants and retail stores without functional degradation.



APEXA® CX Features



Ultra thin bezel



High Performance



SATA SSD



Useful I/O ports

APEXA® CX System

APEXA® CX

System

Processors	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Alder Lake-N
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)
Storage	SATA 3 (6GB/s) 2.5 inch SSD 64GB, Support AHCI
Audio	HD Audio Codec
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher
TPM	TPM 2.0


APEXA® CX



Powerful performance

APEXA® CX Display

15"



APEXA® CX

Display

Type	15" TFT LCD, LED Backlight
Resolution	1024 x 768
Brightness	450 cd/m ² (Typ.)
Touchscreen	Projected Capacitive Touch

Interface

Display	1 x miniDP (With Power Output)
USB	6 (2 x USB 3.0, 4 x USB 2.0)
Serial	4 (COM1, DB9, Full Signal, with 5V/12V Power Output on 9 Pins, BIOS COM2, RJ-45, Full Signal, with 5V/12V Power Output on 1 Pins, BIOS COM3, RJ-45, Full Signal COM5, DB9, Full Signal)
LAN	1 x Gigabit Ethernet (RJ-45)
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)
Audio Port	1 x Line out
Speaker	1 x 1W (Mono, Factory Option)

Power

Power Supply	Adapter 12V, 5A (DIN 4 Pin Jack)
--------------	----------------------------------

APEXA® CX Interface & Option & Peripherals

APEXA® CX

Physical & Environmental



Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	351 x 206 x 308 (mm), 13.8 x 8.11 x 13.8 (in)
Packing Dimensions (W x D x H)	435 x 165 x 485 (mm), 17.1 x 6.5 x 19.1 (in)
Net Weight	4,410g, 9.7 lbs
Packing Weight	5,500g, 12.1 lbs
Certification	CE, FCC, KC
Color	Dark Grey / White

Options & Peripherals

Optional Display	- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)
Storage	- 2.5 inch SSD 128GB, HDD 500GB, 1TB - NVMe M.2 2242-D2-M, 128GB
MSR	Comply with ISO 7811, Support 1/2/3 Track
Smart Card Reader	EMV Level 1
Key Reader	Supported, Dallas i-Button Reader
Fingerprint Reader	Supported
Wall Mounting	VESA, 75 x 75 (mm), 100 x 100 (mm)
Serial Conversion Cable	RJ-45 to D-sub 9

*Specifications may change without prior notice.

APEXA® CX I/O Ports

												
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩	⑪	⑫	⑬
① COM1	② COM2	③ COM3	④ miniDP	⑤ POWER connector						⑪ Cash Drawer		
					⑥ LAN	⑦ USB	⑧ COM5	⑨ MSR	⑩ AUDIO		⑫ USB	⑬ USB

APEXA®

APEXA®'s unrivaled innovative design enables customers to enjoy space efficiency and usability at the same time. APEXA® features powerful performance, superior touch display, multiple I/O interfaces and flexible installation.




APEXA® Features



! Compact, modern design



! OS Support



! Multiple I/O Interfaces



! Flexible installation

APEXA® System

	APEXA® RL	APEXA® AP	APEXA® AN	APEXA® A2
System				
	Windows			Android
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-1335U Processor 12M Cache, up to 4.60 GHz	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N	-
Memory	4GB Standard (DDR43200 MT/s, Socket 1 x SODIMM, Max. 96GB)	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 32GB),	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB),	4GB Standard, LPDDR4
Storage	Form factor : SATA 3 (6GB/s) 2.5 inch SSD 64GB, Support AHCI			eMMC 32GB (Max.64GB)
RAID	RAID 0,1		Not supported	
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher			Android 9.0/ 12
TPM	TPM 2.0			Not Supported

APEXA®



Superior performance



Powerful performance



Efficient performance

APEXA® Display

21.5"




15.6"FH



15.6"



15"




	APEXA® RL	APEXA® AP	APEXA® AN	APEXA® A2
Display				
	APEXA® RL-2150	APEXA® AP-2150	APEXA® AN-2150	APEXA® A2-2150
Type	21.5" TFT LCD, LED Backlight			
Resolution	1920 x 1080			
Brightness	300 cd/m ² (typ.)			
Touchscreen	Projected Capacitive Touch			
	APEXA® RL-1560FH	APEXA® AP-1560FH	APEXA® AN-1560FH	APEXA® A2-1560FH
Type	15.6" TFT LCD, LED Backlight			
Resolution	1920 x 1080			
Brightness	400 cd/m ² (typ.)			
Touchscreen	Projected Capacitive Touch			
	APEXA® RL-1560	APEXA® AP-1560	APEXA® AN-1560	APEXA® A2-1560
Type	15.6" TFT LCD, LED Backlight			
Resolution	1366 x 768			
Brightness	400 cd/m ² (typ.)			
Touchscreen	Projected Capacitive Touch			
	APEXA® RL-1500	APEXA® AP-1500	APEXA® AN-1500	APEXA® A2-1500
Type	15" TFT LCD, LED Backlight			
Resolution	1024 x 768			
Brightness	300 cd/m ² (typ.)			
Touchscreen	Projected Capacitive Touch			

APEXA® Interface

	APEXA® RL	APEXA® AP	APEXA® AN	APEXA® A2
Interface				
Display	1 x VGA (With Power Output)			
USB	4 (2 x USB 3.0, 2 x USB 2.0)			
Serial	4 (COM 1, with 5V/12V Power Output on 9 Pins, BIOS COM2~3, RJ-45, Full Signal COM4, RJ-12, Only Tx/Rx, 12V Power Output, Reserved for CDP COM6, RJ-45, Only Tx/Rx, 5V Power Output, Reserved for MSR)			
LAN	1 x Gigabit Ethernet (RJ-45)			
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)			
Audio Port	1 x Line out			
Speaker	2 x 1W (Stereo, Factory Option)			
Power				
Power Supply	- 24V, 2.5A (DIN 3 Pin Jack, Normal) - 24V, 6.35A (Powered USB Option)			

APEXA® I/O Ports



APEXA® Physical & Environmental

	APEXA® RL	APEXA® AP	APEXA® AN	APEXA® A2
Physical & Environmental				
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity			
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity			
	APEXA® RL-2150	APEXA® AP-2150	APEXA® AN-2150	APEXA® A2-2150
Dimensions (W x D x H)	520 x 200 x 339 (mm), 20.4 x 7.9 x 13.3 (in)			
Packing Dimensions (W x D x H)	640 x 300 x 465 (mm), 25.2 x 11.8 x 18.3 (in)			
Net Weight	6,900kg, 15.21 lbs			
Packing Weight	11,300kg, 24.91 lbs			
	APEXA® RL-1560FH	APEXA® AP-1560FH	APEXA® AN-1560FH	APEXA® A2-1560FH
Dimensions (W x D x H)	400 x 210 x 311 (mm), 15.7 x 8.3 x 12.2 (in)			
Packing Dimensions (W x D x H)	500 x 300 x 470 (mm), 19.6 x 11.8 x 18.5 (in)			
Net Weight	5,000g, 15.43 lbs			
Packing Weight	9,000g, 19.84 lbs			
	APEXA® RL-1560	APEXA® AP-1560	APEXA® AN-1560	APEXA® A2-1560
Dimensions (W x D x H)	400 x 210 x 311 (mm), 15.7 x 8.3 x 12.2 (in)			
Packing Dimensions (W x D x H)	500 x 300 x 470 (mm), 19.6 x 11.8 x 18.5 (in)			
Net Weight	5,000g, 15.43 lbs			
Packing Weight	9,000g, 19.84 lbs			
	APEXA® RL-1500	APEXA® AP-1500	APEXA® AN-1500	APEXA® A2-1500
Dimensions (W x D x H)	364 x 210 x 333 (mm), 14.3 x 8.2 x 13.1 (in)			
Packing Dimensions (W x D x H)	500 x 300 x 470 (mm), 19.6 x 11.8 x 18.5 (in)			
Net Weight	5,300g, 11.68 lbs			
Packing Weight	8,000g, 17.63 lbs			
	APEXA® RL	APEXA® AP	APEXA® AN	APEXA® A2
Certification	CE, FCC, KC			
Color	Dark Grey, High Gloss White			

APEXA® Options & Peripherals

	APEXA® RL	APEXA® AP	APEXA® AN	APEXA® A2
Options & Peripherals				
Optional Display	2nd Display : 9.7" (1024 x 768) 2nd Display : 15" (1024 x 768) VFD : 2 Lines x 20 Columns			
Optional I/O Board	- Option 1 : 1 x Gigabit Ethernet (RJ-45) + 2 x USB 2.0 (Factory option) - Option 2 : 1 x 12V Powered USB 2.0 + 1 x 24V Powered USB 2.0 (Factory option) - Option 3 : 1 x 12V Powered USB 2.0 + 1 x 12V Powered USB 2.0 (Factory option) - Option 4 : 1 x 24V Powered USB 2.0 + 1 x 24V Powered USB 2.0 (Factory option) - Option 5 : 1 x 12V Powered USB 2.0 + 2 x USB 2.0 (Factory option) - Option 6 : 1 x 24V Powered USB 2.0 + 2 x USB 2.0 (Factory option) - Option 7 : 1 x COM5 (RJ-45, Full signal) + 2 x USB 2.0 (Factory option) - Option 8 : 4 x USB 2.0 (Factory option)			
Storage	- Default: 2.5 inch SSD 128GB, HDD 500GB, 1TB - Option: M.2 2242-D2-M(SATA or NVMe)			
Wi-Fi / BT	M.2 for Wi-Fi/BT (Factory option)			
MSR	Comply with ISO 7811, Support 1/2/3 Track			
Smart Card Reader	EMV Level 1			
Key Reader	Supported, Dallas i-Button Reader			
Fingerprint Reader	Supported			
Wall Mounting	VESA, 75 x 75 (mm), 100 x 100 (mm)			
Serial Conversion Cable	RJ-45 to D-sub 9			-

*Specifications may change without prior notice.

APEXA® Options



2nd DISPLAY



VFD



MSR

APEXA® X

APEXA X is equipped with a compact monitor screen and can perform various powerful functions required in the retail and restaurant industries with the Intel N97 that uses Intel's 12th generation Alder Lake.



APEXA® X Features



Compact, modern design



OS Support



Mini DP Port



Flexible installation

APEXA® X System

APEXA® X	
System	
Processors	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz
Chipset	Intel® Alder Lake-N
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)
Storage	Form factor : SATA 3 (6GB/s) 2.5 inch SSD 64GB, Support AHCI
Audio	HD Audio Codec
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher
TPM	TPM 2.0

APEXA® X



Powerful performance

APEXA® X Display

15"



APEXA® X

Display

	APEXA® X-1500
Type	15" TFT LCD, LED Backlight
Resolution	1024 x 768
Brightness	300 cd/m ² (typ.)
Touchscreen	Projected Capacitive Touch

Interface

Display	1 x Displayport (miniDP/ With Power Output)
USB	6 (2 x USB 3.0, 4 x USB 2.0)
Serial	4 (COM1, Dsub-9, with 5V/12V Power Output on 9 Pins, BIOS COM2~3, RJ-45, Full Signal COM5, Dsub-9, Full Signal)
CashDrawer Port	1 x Gigabit Ethernet (RJ-45)
LAN	1 x RJ-12 (Integrated circuit GPIO)
Audio Port	1 x Line out
Speaker	2 x 1W (Stereo) (Factory Option)

Power

Power Supply	Adapter 12V, 5A (DIN 4 Pin Jack)
--------------	----------------------------------

APEXA® X Interface I Option & Peripherals

APEXA® X

Physical & Environmental

	APEXA® X-1500
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	364 x 210 x 333 (mm), 14.3 x 8.2 x 13.1 (in)
Packing Dimensions (W x D x H)	500 x 300 x 470 (mm), 19.6 x 11.8 x 18.5 (in)
Net Weight	5,300g, 11.68 lbs
Packing Weight	8,000g, 17.63 lbs
Certification	CE, FCC, KC
Color	Dark Grey / High Gloss White

Options & Peripherals

Optional Display	- 2nd Display : 9.7" (1024 x 768) - 2nd Display : 15" (1024 x 768) - VFD : 2 Lines x 20 Columns
Storage	- 2.5 inch SSD 128GB, HDD 500GB, 1TB - NVMe M.2 2242-D2-M, 128GB
Wi-Fi / BT	M.2 for Wi-Fi/BT (Factory option)
MSR	Comply with ISO 7811, Support 1/2/3 Track
Smart Card Reader	EMV Level 1
Key Reader	Supported, Dallas i-Button Reader
Fingerprint Reader	Supported
Wall Mount Kit	VESA, 75 x 75 (mm), 100 x 100 (mm)
Serial Conversion Cable	RJ-45 to D-sub 9

*Specifications may change without prior notice.

EDGE

EDGE was born with an ultra-slim design and a fanless structure. It supports both Android and Windows operating systems with the latest CPUs, supporting GMS authentication and MDM solutions. It boasts a slimmer and more edgy design and is a POS device loved by various industries such as restaurants and retail.




EDGE Features



| OS supported



| Efficient use of heat sink



| GMS Certification



| Slim, sleek design

EDGE System

EDGE

System

	EDGE AP	EDGE AN	EDGE Q	EDGE A4	EDGE A2
Processors	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz	QCS6490 Kryo670 1 x Gold @ 2.7GHz, 3 x Gold @ 2.4GHz, 4 x Silver@1.95GHz	RK3576 Quad Cortex-A72 @ 2.2 GHz Quad Cortex-A53 @ 2.0 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Alder Lake-P	Intel Alder Lake-N	-	-	-
Memory	4GB (DDR4 3200 MT/s, Max 64GB)	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)	DDR4 6GB (Max 16GB)	DDR4 6GB (Max 16GB)	4GB Standard, LPDDR4, On-board
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 1 x NVMe M.2 2242 128GB (Factory default)		UFS 128GB (Max 128GB)	eMMC 128GB (Max 128GB)	eMMC 32GB, On-board (Max.64GB)
Audio	HD Audio Codec				
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher		Android 13	Android 14 GMS	Android 9 / 12 GMS
TPM	TPM 2.0		N/A		

EDGE



Windows



ANDROID



EDGE Display I Interface

15.6"



EDGE

Display

Type	15.6" TFT LCD, LED Backlight (eDP Interface)
Resolution	1920 x 1080
Brightness	350 cd/m ²
Response	20ms
Contrast Ratio	1200 (Typ.)
Touchscreen	Projected Capacitive Touch

Interface

	EDGE AP	EDGE AN	EDGE Q	EDGE A4	EDGE A2
Display	1 x Displayport (miniDP)				
Interface	eDP				
USB	4 (2 x USB 3.0, 2 x USB 2.0)		5 (1 x USB C-Type, 4 x USB 2.0)		
Serial	2 (COM1~2, RJ-45, Full Signal)		1 (COM3, RJ-45, Full Signal)		
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)				
LAN	1 x Gigabit Ethernet (RJ-45)				
Wi-Fi / BT	N/A		Wi-Fi 2.4G/5G, BT 5.3 Combo MIMO		Wi-Fi 2.4G/5G, BT 5.0 Combo
Speaker	1 x 1W (Mono)				
Audio Port	1 x Line-out				

Power

Power Supply	Adaptor 12V, 5A(C-Type Plug)	Adapter 12V, 5A (DIN 4 Pin Jack)
--------------	------------------------------	----------------------------------

EDGE I/O Ports

Windows									
Android									

EDGE Physical & Environmental

EDGE

Physical & Environmental

Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	367 x 180 x 289 (mm), 14.4 x 7 x 11.4 (in)
Packing Dimensions (W x D x H)	455 x 163 x 308 (mm), 17.9 x 6.4 x 12.1 (in)
Net Weight	3,330g, 7.35 lbs
Packing Weight	5,030g, 11.09 lbs
Certification	CE, FCC, KC
Color	Space Grey / White / Black

EDGE Option & Peripherals

EDGE

Options & Peripherals

Optional Display	- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)				
Optional I/O Box	- USB 2.0 x 2 (Factory option) - Option 1 : 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) - Option 2 : 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 3 : 1 x 12V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 4 : 6 x USB 2.0 / 2 x RJ45 (Full Signal)				
MSR	Comply with ISO 7811, Support 1/2/3 Track				
Smart Card Reader	EMV Level 1				
	EDGE AP	EDGE AN	EDGE Q1	EDGE A4	EDGE A2
NFC Reader	N/A		2nd Display (Optional)		Not supported
Key Reader	Dallas i-button Reader				
Fingerprint	Supported				
GPS	N/A		Factory Option		Not supported
Wall Mount Kit	VESA, 75 x 75 (mm), 100 x 100 (mm)				
Serial Conversion Cable	RJ-45 to D-sub 9				

*Specifications may change without prior notice.

ACT


ACT is an Android-based POS equipped with the latest Android 12 version, and can manage devices safely and efficiently with GMS authentication and mobile device management solutions. ACT also implements efficient performance by mounting the latest Intel processor, a Windows operating system.



ACT Features



| OS Support



| GMS Certification



| Slim, sleek design



| External I/O box

ACT System

ACT				
System				
	ACT AN	ACT Q	ACT A4	ACT A2
Processors	Intel® Processor N97 6M Cache, up to 3.60 GHz Intel® Processor N95 6M Cache, up to 3.60 GHz	QCS6490 Kryo670 1 x Gold @ 2.7GHz, 3 x Gold @ 2.4GHz, 4 x Silver @ 1.95GHz	RK3576 Quad Cortex-A72 @ 2.2 GHz Quad Cortex-A53 @ 2.0 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel Alder Lake-N	N/A		
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)	DDR4 6GB (Max 32GB)	DDR4 6GB (Max 16GB)	LPDDR4, 4GB Standard, On-board
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 1 x NVMe M.2 2242 128GB (Factory default)	UFS 128GB (Max 128GB)	eMMC 128GB (Max 128GB)	eMMC 32GB, On-board (Max.64GB)
Audio	HD Audio Codec			
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher	Android 13	Android 14 GMS	Android 9 / 12 GMS
TPM	TPM 2.0	N/A		

ACT



ACT Display I Interface

15.6"



ACT

Display

Type	15.6" TFT LCD, LED Backlight (eDP Interface)
Resolution	1920 x 1080
Brightness	350 cd/m ²
Response	20ms
Contrast Ratio	1200 (Typ.)
Touchscreen	Projected Capacitive Touch

Interface

	ACT AN	ACT Q	ACT A4	ACT A2
Display	1 x Displayport (miniDP)			
Interface	eDP			
USB	4 (2 x USB 3.0, 2 x USB 2.0)	5 (1 x USB C-Type, 4 x USB 2.0)		
Serial	2 (COM1~2, RJ-45, Full Signal)	1 (COM3, RJ-45, Full Signal)		
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)			
LAN	1 x Gigabit Ethernet (RJ-45)			
Wi-Fi / BT	N/A	Wi-Fi 2.4G/5G, BT 5.3 Combo MIMO		Wi-Fi 2.4G/5G, BT 5.0 Combo
Audio Port	1 x Line-out			
Speaker	1 x 1W (Mono)			

Power

Power Supply	Adaptor 12V, 5A(C-Type Plug)	Adaptor 12V, 5A (DIN 4 Pin Jack)
--------------	------------------------------	----------------------------------

ACT I/O Ports

Windows										
		① AUDIO	② USB 3.0	③ LAN	④ COM1	⑤ Drawer Kicker	⑥ POWER	⑦ COM2	⑧ USB 2.0	⑨ 2nd Display
Android										
		① AUDIO	② USB 2.0	③ COM1	④ POWER	⑤ Drawer Kicker	⑥ USB-C	⑦ LAN	⑧ USB 2.0	⑨ 2nd Display

ACT Physical & Environmental

ACT	
Physical & Environmental	
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	367 x 180 x 289 (mm), 14.4 x 7 x 11.4 (in)
Packing Dimensions (W x D x H)	455 x 308 x 163 (mm), 17.9 x 12.1 x 6.4 (in)
Net Weight	2,950g, 6.5 lbs
Packing Weight	5,000g, 11 lbs
Certification	CE, FCC, KC
Color	Dark Grey / White

ACT Option & Peripherals

ACT			
Options & Peripherals			
Optional Display	- 2nd Display (9.7" (1024 x 768)) - 2nd Display (10.1" (1280 x 800)) - 2nd Display (15" (1024 x 768)) - 2nd Display (15.6" (1920 x 1080)) - VFD (2 Lines x 20 Columns)		
Optional I/O Box	- USB 2.0 x 2 (Factory option) - Option 1 : 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) - Option 2 : 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 3 : 1 x 12V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) - Option 4 : 6 x USB 2.0 / 2 x RJ45 (Full Signal)		
MSR	Comply with ISO 7811, Support 1/2/3 Track		
Smart Card Reader	EMV Level 1		
NFC Reader	N/A	2nd Display (Optional)	Not supported
Key Reader	Dallas i-button Reader		
Fingerprint Reader	Yes		
GPS	N/A	Factory Option	Not supported
Wall Mount Kit	VESA-Compatible, 75 x 75 (mm), 100 x 100 (mm)		
Serial Conversion Cable	RJ-45 to D-sub 9		

*Specifications may change without prior notice.

MINT

MINT is a compact and powerful all-in-one POS terminal that allows payment and receipt printing with a single terminal. It features 10.1-inch screen display that can interchange directions for sign pad use with a simple tilt of a screen.



MINT Features



■ All-in-One



■ Tilting screen / Signpad



■ OS Support



■ 10.1" Compact size

MINT System

MINT

System

	MINT TL	MINT EL	MINT A2
Processor	Intel® Processor N150 6M Cache, up to 3.60 GHz	Intel® Celeron® Processor J6412 1.5M Cache, up to 2.60 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Twin Lake	Intel® Elkhart Lake	-
Memory	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 16GB)	4GB Standard (DDR4 3200 MT/s, Socket 1 x SODIMM, Max. 32GB)	4GB Standard, LPDDR4, On-board
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 1 x NVMe M.2 2242 128GB (Factory default)		eMMC 32GB, On-board (Max.64GB)
Audio	HD Audio Codec		
Built-in Printer	3" Jam-Free Thermal, Max. 250mm/s, Auto Cutter, Built-in Type		
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H2 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher		Android 9 / 12 GMS
TPM	TPM 2.0		N/A

MINT






Powerful performance



Efficient performance

MINT Dimensions



(Unit:mm)

MINT Display | Interface

10.1"



MINT

Display

Type	10.1" TFT LCD, LED Backlight
Interface	LVDS
Resolution	1280 x 800
Brightness	400 cd/m ²
Response	29ms
Contrast Ratio	800 (Typ.)
Touchscreen	Projected Capacitive Touch

Interface

	MINT TL	MINT EL	MINT A2
USB	5 (4 x USB 2.0, 1 x USB C-Type)		
Serial	4 (COM1~2, RJ-45, Full Signal) (COM3~4, RJ-12, Only Tx/Rx)		
CashDrawer Port	1 x RJ-12 (Integrated circuit GPIO)		
LAN	1 x Gigabit Ethernet (RJ-45)		
Wi-Fi / BT	N/A		Wi-Fi 2.4G/5G, BT 5.0 Combo (Factory Option)
Speaker	1 x 1W (Mono)		

Power

Power Supply	Adaptor 24V / 2.5A (DIN 3 Pin Jack)
--------------	-------------------------------------

MINT Physical & Environmental | Options & Peripherals

MINT

Physical & Environmental


Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	244 x 200 x 172 (mm), 9.6 x 8 x 6.8 (in)
Packing Dimensions (W x D x H)	320 x 330 x 316 (mm), 12.6 x 13 x 12.4 (in)
Net Weight	2,420g, 5.3 lbs
Packing Weight	4,200g, 9.26 lbs
Certification	CE, FCC, KC
Color	Black, White


Options & Peripherals

MSR	Comply with ISO 7811, Support 1/2/3 Track
Smart Card Reader	EMV Level 1 (Factory option)
NFC Reader	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693

*Specifications may change without prior notice.

MINT I/O Ports





Windows

① USB-C ② COM1 ③ COM2 ④ COM3 ⑤ COM4 ⑥ USB 2.0
⑦ USB 2.0 / USB 3.0 ⑧ Drawer Kicker ⑨ DC 24V ⑩ LAN

Android


① USB-C ② COM1 ③ COM2 ④ COM3 ⑤ COM4 ⑥ USB 3.0
⑦ USB 2.0 ⑧ Drawer Kicker ⑨ DC 24V ⑩ LAN

PTM


The PTM 2150 is a type of panel PC. This kiosk or touch monitor eliminates payment modules and other accessories, maximizing cost-effectiveness while maintaining a minimalist design. Equipped with a 21.5" FHD industrial LED panel, it delivers a bright, clear display with low power consumption. It can be used in a variety of environments, including smart factory operation control and monitoring PCs, exhibitions, and digital signage for video.



PTM Features




FHD LED panel



Ultra-slim



I/O scalability



Wall mount

PTM System

PTM

System

Processors	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	-
Memory	DDR4 4GB Standard, On-board
Storage	eMMC 32GB, On-board (Max.64GB)
Audio	HD Audio Codec
RAID	Not supported
Operating Systems	Android 9 / 12 (GMS)

PTM



Efficient performance

PTM Display | Interface

21.5"



PTM

Display

	PTM A2-2150
Type	21.5" TFT LCD, LED Backlight
Resolution	1080 x 1920
Brightness	250 cd/m ²
Response	14ms
Contrast Ratio	1000 (Typical)
Touchscreen	Projected Capacitive Touch

Interface

USB	Default : 2(2 x USB 2.0) Extension : 4(2 x USB 2.0, 2 X USB 3.0)
Serial	Default : Not supported Extension : 2 (COM1~2, RJ-45 Full Signal)
LAN	1 x Gigabit Ethernet (RJ-45)
Wi-Fi / BT	Wi-Fi 2.4G/5G, BT 5.0 Combo
Audio Port	Default : Not supported Extension : 1 x Line out
Speaker	1 x 5W (Mono)

Power

Power Supply	Adaptor 24V/6.35A, DIN 3 Pin Jack
--------------	-----------------------------------

PTM Physical & Environmental

PTM	
Physical & Environmental	
	PTM A2-2150
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~60 °C at 10% to 90% Humidity
Dimensions (W x D x H)	312.6 x 40.5 x 521 (mm), 12.3 x 1.59 x 20.5 (in)
Packing Dimensions (W x D x H)	635 x 160 x 436 (mm), 25 x 6.29 x 17.16 (in)
Net Weight	5,050g, 11.13 lbs
Packing Weight	7,840g, 17.26 lbs
Certification	CE, FCC, KC
Color	Black / White
Options & Peripherals	
Antenna	1 x External Antenna (Wi-Fi 2.4G/5G)

*Specifications may change without prior notice.

PTC

PTC is an open frame panel PC which is widely applied as a smart factory operation control or monitoring PC and is also configured for exhibitions and video digital signage.



PTC Features



| 21.5"/ 15.6"/ 15"



| Options
(Scanner, MSR/SCR, NFC etc.)



| Space saving



| Easy cable routing and management

PTC System

	PTC RL	PTC AP	PTC AN
System			
Processors	Intel® Core™ i3-1315U Processor 10M Cache, up to 4.50 GHz Intel® Core™ i5-1335U Processor 12M Cache, up to 4.60 GHz	Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz
Chipset	Intel® Raptor Lake	Intel® Alder Lake-P	Intel® Alder Lake-N
Memory	4GB Standard (Max. 32GB), DDR4 3200 MT/s, Socket 1 x SODIMM		4GB Standard (Max. 16GB), DDR4 3200 MT/s, Socket 1 x SODIMM
Storage	SATA 3 (6GB/s) 2.5 inch SSD 64GB, Support AHCI	SATA 3 (6GB/s) 2.5 inch SSD 64GB, Support AHCI	SATA 3 (6GB/s) 2.5 inch SSD 64GB, Support AHCI
RAID	RAID 0,1		-
Operating Systems	Windows 10 IoT LTSC 21H1 Windows 11 IoT LTSC 24H2		
TPM	Support		
Audio	HD Audio Codec		

PTC




Superior performance






Powerful performance

PTC Dimensions




PTC Display


21.5"



15.6"



15"



	PTC RL	PTC AP	PTC AN
Display			
	PTC RL-2150	PTC AN-2150	PTC EL-2150
Type	21.5" TFT LCD, LED Backlight		
Resolution	1920 x 1080		
Brightness	250 cd/m ² (typ.)		
Touchscreen	Projected Capacitive Touch		
	PTC RL-1560	PTC AN-1560	PTC EL-1560
Type	15.6" TFT LCD, LED Backlight		
Resolution	1366 x 768 / 1920 x 1080		
Brightness	400 cd/m ² (typ.)		
Touchscreen	Projected Capacitive Touch		
	PTC RL-1500	PTC AN-1500	PTC EL-1500
Type	15.0" TFT LCD, LED Backlight		
Resolution	1024 x 768		
Brightness	300 cd/m ² (typ.)		
Touchscreen	Projected Capacitive Touch		
Interface			
Display	1 x VGA (With Power Output)		
USB	4 (2 x USB 3.0, 2 x USB 2.0)		
Serial	4 (COM1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2~3, RJ-45, Full Signal) (COM5, Full Signal)		
LAN	1 x Gigabit Ethernet (RJ-45)		
Audio Port	1 x Line-out		
Speaker	2 x 1W (Stereo) (Factory Option)		
Power			
Power Supply	Adaptor 24V, 2.5A(3 Pin DIN Jack) When applying Option 2, 3, 4, use adaptor 24V/6.35A		

PTC Physical & Environmental

	PTC RL	PTC AP	PTC AN
Physical & Environmental			
	PTC RL-2150	PTC AN-2150	PTC EL-2150
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity		
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity		
Dimensions	530.6 x 322.1 x 49.05 (mm)		
Packing Dimensions	608 x 400 x 100 (mm), 23.9 x 15.7 x 3.9 (in)		
Net Weight	6,000g, 13.23 lbs		
Packing Weight	6,500g, 14.33 lbs		
	PTC RL-1560	PTC AN-1560	PTC EL-1560
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity		
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity		
Dimensions	400 x 37.4 x 241 (mm) / 15.7 x 1.47 x 9.5 (in)		
Packing Dimensions	608 x 400 x 100 (mm), 23.9 x 15.7 x 3.9 (in)		
Net Weight	3,390g, 7.5 lbs		
Packing Weight	3,700g, 8.2 lbs		
	PTC RL-1500	PTC AN-1500	PTC EL-1500
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity		
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity		
Dimensions	530.6 x 322.1 x 49.05 (mm)		
Packing Dimensions	608 x 400 x 100 (mm), 23.9 x 15.7 x 3.9 (in)		
Net Weight	3,500g, 7.72 lbs		
Packing Weight	4,700g, 10.36 lbs		
	PTC RL	PTC AP	PTC AN
Certification	TBD		
Color	Matte Black		

Options & Peripherals

Optional I/O Board	- Option 1 : 1 x Gigabit Ethernet (RJ-45) + 2 x USB 2.0 (Factory option) - Option 2 : 1 x 12V Powered USB 2.0 + 1 x 24V Powered USB 2.0 (Factory option) - Option 3 : 1 x 12V Powered USB 2.0 + 1 x 12V Powered USB 2.0 (Factory option) - Option 4 : 1 x 24V Powered USB 2.0 + 1 x 24V Powered USB 2.0 (Factory option) - Option 5 : 1 x 12V Powered USB 2.0 + 2 x USB 2.0 (Factory option) - Option 6 : 1 x 24V Powered USB 2.0 + 2 x USB 2.0 (Factory option) - Option 7 : 1 x COM5 (RJ-45, Full signal) + 2 x USB 2.0 (Factory option) - Option 8 : 4 x USB 2.0 (Factory option)
Storage	2.5 inch SSD 128GB, HDD 500GB, 1TB
Wi-Fi / BT	USB to WiFi Module (Factory Option), M.2 for WiFi/BT
Wall Mount Kit	VESA-Compatible, 100 x 100 (mm), 100 x 200 (mm)
Serial Conversion Cable	RJ-45 to D-sub 9

*Specifications may change without prior notice.

KDS

KDS (Kitchen Display System) is a digital solution that helps kitchen staff manage orders, track progress, and improve efficiency. It features a durable, waterproof design, enhanced wireless range, and anti-glare and anti-fingerprint technologies for better usability in busy environments.



KDS Features



Antenna



PoE



Anti-Glare & Fingerprint



IP 54


KDS System

	KDS AN	KDS Q	KDS A4	KDS A2
System				
Processors	Intel® Processor N97 6M Cache, up to 3.60 GHz	QCS6490 Kryo670 1 x Gold @ 2.7GHz, 3 x Gold @ 2.4GHz, 4 x Silver @ 1.95GHz	RK3576 Quad Cortex-A72 @ 2.2 GHz Quad Cortex-A53 @ 2.0 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Alder Lake-N	N/A		
Memory	4GB (DDR4 3200 MT/s, Max 16GB)	LPDDR4 6GB (Max 32GB)	LPDDR4 6GB (Max 16GB)	LPDDR4 4GB Standard
Storage	Form factor : NVMe M.2 2242-D2-M (No capacity limit) Mountable : 1 x NVMe M.2 2242 128GB (Factory default)	UFS 128GB (Max 128GB)	eMMC 128GB (Max 128GB)	eMMC 32GB, On-board (Max.64GB)
Audio	HD Audio Codec			
Operating Systems	Windows 10 IoT Enterprise LTSC Ver. 21H1 or higher Windows 11 IoT Enterprise LTSC Ver. 24H2 or higher	Android 13 GMS	Android 14 GMS	Android 9 / 12 GMS
TPM	Support	N/A		

KDS




KDS Dimensions




KDS Display | Interface

27"



21.5"



	KDS AN	KDS Q	KDS A4	KDS A2
Display				
	KDS AN-2700	KDS Q-2700	KDS A4-2700	KDS A2-2700
Type	27" TFT LCD, LED Backlight			
Interface	LVDS			
Resolution	1920 x 1080			
Brightness	300 cd/m² (typ.)			
Response	12 ms			
Contrast Ratio	3000 (typ.)			
Touchscreen	Projected Capacitive Touch			
	KDS AN-2150	KDS Q-2150	KDS A4-2150	KDS A2-2150
Type	21.5" TFT LCD, LED Backlight			
Interface	LVDS			
Resolution	1920 x 1080			
Brightness	250 cd/m² (typ.)			
Response	22 ms			
Contrast Ratio	1000 (typ.)			
Touchscreen	Projected Capacitive Touch			
Interface				
Display	Out : 1 x HDMI 1.2			
USB	4 (2 x USB 3.0, 2 x USB 2.0)			
Serial	2 (COM1~2, RJ-45, Full Signal)			
LAN	1 x Gigabit Ethernet (RJ-45)			
Wi-Fi / BT	KDS AN : Wi-Fi 2.4G/5G (MIMO) / BT 5.2 KDS Q / A4 : Wi-Fi 2.4G/5G, BT 5.3 Combo MIMO KDS A2 : Wi-Fi 2.4G/5G, BT 5.0 Combo			
Audio Port	1 x Line out			
Speaker	KDS AN / Q / A4 / A2 2700 : 2 x 3W (Stereo) KDS AN / Q / A4 / A2 2150 : 1 x 1W (Mono)			
Power				
Power Supply	- Adaptor 24V, 2.5A (DIN 3 Pin Jack) - AC Inlet Socket - PoE++ 12V, 5A			

KDS Physical & Environmental

	KDS AN	KDS Q	KDS A4	KDS A2
Physical & Environmental				
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity			
Storage Temperature	-20 °C ~60 °C at 10% to 90% Humidity			
IP Grade	IP54			
	KDS AN-2700	KDS Q-2700	KDS A4-2700	KDS A2-2700
Dimensions (W x D x H)	636.8 x 46 x 387 (mm), 25.1 x 1.8 x 15.2 (in)			
Packing Dimensions (W x D x H)	760 x 160 x 517 (mm), 29.9 x 6.29 x 20.3 (in)			
Net Weight	8,300g, 18.3 lbs			
Packing Weight	9,700g, 21.4 lbs			
	KDS AN-2150	KDS Q-2150	KDS A4-2150	KDS A2-2150
Dimensions (W x D x H)	520 x 46 x 315 (mm), 20.4 x 1.8 x 12.4 (in)			
Packing Dimensions (W x D x H)	645 x 160 x 445 (mm), 25.3 x 6.29 x 17.5 (in)			
Net Weight	6,000g, 13.2 lbs			
Packing Weight	7,600g, 16.8 lbs			
	KDS AN	KDS Q	KDS A4	KDS A2
Certification	CE, FCC, KC			
Color	Black			

Options & Peripherals

Camera	Supported
Bump Bar	20 key, USB Interface
MSR	Comply with ISO 7811, Support 1/2/3 Track
Smart Card Reader	EMV Level 1
Antenna	Wi-Fi External Antenna (2 x 2)
LED Light Bar	Supported
Wall Mount Kit	VESA-Compatible 100 x 100 (mm), (W x D x H) 186 x 22 x 168 (mm)

*Specifications may change without prior notice.

PAI TAB

The PAI TAB is a 10.1-inch POS tablet designed to enhance store operational efficiency and customer experience. Its slim, compact design features an octa-core processor for reliable, fast performance. The server can be used as a portable tableside ordering device or combined with the cradle to function as a stationary ordering station.



PAI TAB Features



Portable / Stationary



POGO pin charging



Wireless connectivity



Charging stand

PAI TAB System


	PAI TAB
System	
Processors	MT8781 Dual-core Cortex-A76 up to 2.2GHz Hexa-core Cortex-A55 up to 2.20GHz
Memory	8GB (LPDDR4 2133 MT/s)
Storage	128GB (UFS 2.1)
Operating Systems	Android 15 GMS
Audio	HD Audio Codec

PAI TAB




Powerful performance

PAI TAB Dimensions



PAI TAB Display

10.1"




PAI TAB	
Display	
Type	10.1" TFT LCD, LED Backlight
Resolution	1280 x 800
Brightness	350 cd/m ²
Touchscreen	Projected Capacitive Touch
Interface	
USB	2 x USB C-Type (1 x USB 2.0, 1 x USB OTG : Host mode only)
Wi-Fi / BT	Wi-Fi 2.4G / 5 G, BT 2.1 Combo module
Speaker	2 x 1W
Camera	Front 5MP, Rear 13MP (Option)
Power	
Power Supply	- Adaptor 5V, 2A (USB C-Type Plug) - Adaptor 5V, 3A (USB C-Type Plug) : Korea

PAI TAB Physical & Environmental

	PAI TAB
Physical & Environmental	
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x H x D)	PAI TAB : 246 x 165 x 11.3 (mm), 9.68 x 6.5 x 0.44 (in) Charging stand : 203.3 x 119 x 87.5 (mm), 8.0 x 4.6 x 3.4 (in)
Packing Dimensions (W x H x D)	PAI TAB : 246 x 165 x 11.3 (mm), 9.68 x 6.5 x 0.44 (in) Charging stand : 203.3 x 119 x 87.5 (mm), 8.0 x 4.6 x 3.4 (in)
Net Weight	PAI TAB : 560g, 1.23 lbs Charging stand : 800g, 1.76 lbs
Packing Weight	TBD
Certification	CE, FCC, KC, JMIC
Color	Black

PAI TAB Charging stand Dimensions



PAI

PAI is a mini kiosk product that allows customers to order and pay at the table. The display can be swiveled and tilted, and built-in battery and external battery options are provided, allowing stable use even in places with limited electrical power.



PAI Features



Swivel 90° / 90°



Tilt 10° & 20°



Built-in & External Battery



Multi Battery Charger

PAI System


	PAI
System	
Processors	MT8788 (Octa-core) Quad-core Cortex-A73 up to 2.0GHz Quad-core Cortex-A53 up to 2.0GH
Memory	4GB (LPDDR4 3200 MT/s, Socket 1 x SODIMM, Max 16GB)
Storage	eMMC 6GB, On-board (Max.64GB)
Operating Systems	Android 12 GMS
Audio	HD Audio Codec

PAI




Powerful performance

PAI Dimensions




PAI Display

10.1"



	PAI
Display	
Type	10.1" TFT LCD, LED Backlight
Resolution	1280 x 800
Brightness	350 cd/m ²
Touchscreen	Projected Capacitive Touch
Interface	
USB	2 (1 x USB 2.0, 1 x USB C-Type)
Wi-Fi / BT	Wi-Fi 2.4G/5G, BT 2.1 Combo module
Speaker	1 x 1W (Mono)
Power	
Power Supply	- Adaptor 5V, 2A(USB C-Type Plug) - Adaptor 5V, 3A(USB C-Type Plug) : Korea

PAI I/O Ports




PAI Physical & Environmental

	PAI
Physical & Environmental	
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	Base body : 240.9 x 34 x 265.3 (mm), 9.5 x 1.3 x 10.4 (in) Stand type : 240.9 x 127 x 269.3 (mm), 9.5 x 5 x 10.6 (in) Clamp type : 240.9 x 38.6 x 360.2 (mm), 9.5 x 1.5 x 14.2 (in)
Packing Dimensions (W x D x H)	420 x 130 x 340 (mm), 16.5 x 5.1 x 13.4 (in)
Net Weight	1,500g, 3.3 lbs
Packing Weight	2,900g, 6.4 lbs
Certification	CE, FCC, KC, JMIC
Color	Black
Options & Peripherals	
Smart Card Reader	EMV Level 1
Wall Mount Kit	TBD

*Specifications may change without prior notice.

PAI Battery Charger Dimensions



MG BOX

MG BOX is designed with an understated size with various I/O ports. It provides maximum performance and extreme durability, enabling it to be used as a POS terminal or a server.



MG BOX Features



Industrial BOX PC



Dual-layer mainboard



High durability and stability



Powered USB support

MG BOX Specifications

	MG BOX
System	
Processors	Intel® Core™ Ultra5 125U 12M Cache, up to 4.3 GHz
Chipset	Intel® Meteor Lake
Memory	4GB Standard (DDR5 5600 MT/s, Socket 2 x SODIMM, Max 64GB)
Storage	Form factor : NVME M.2 2242-D2-M (Support AHCI, No capacity limit.) Mountable : 1 x NVMe M.2 2242 128GB, Up to 1 units can be installed
RAID	RAID 0,1
Audio	HD Audio Codec
Operating Systems	Windows 10 Ver. 21H1 or higher Windows 11 LTSC Ver. 24H2 or higher
TPM	TPM 2.0

MG BOX




Superior performance

MG BOX Specifications


	MG BOX
Interface	
Display	3 (2 x HDMI, 1 x USB Type C (Alt-mode))
USB	9 (4 x USB 3.0, 3 x USB 2.0, 1 x USB Type C (Alt-mode), 1 x USB Type C)
Serial	1 (COM1, RJ45, with DTR/12V Power Output on Pin6, Bios) : RS-232/RS-422/RS-485, Bios (Default : RS-232) optional
LAN	1 x 1 Gigabit Ethernet (RJ-45, Intel® I219-LM) 1 x 2.5 Gigabit Ethernet (RJ-45)
Audio Port	1 x Line out
Extension Slot	1 x Mini PCIe for Wireless LAN/BT/LTE
Power	
Power Supply	Adaptor 12V / 5A DIN 3Pin Jack
Physical & Environmental	
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	209 x 193 x 57 (mm), 8.2 x 7.6 x 2.2 (in)
Packing Dimensions (W x D x H)	340 x 80 x 220 (mm), 13.4 x 3.1 x 8.7 (in)
Net Weight	1,090g, 2.4 lbs.
Packing Weight	2,800g, 6.17 lbs.
Certification	CE, FCC, KC
Color	Dark Grey
Options & Peripherals	
Optional I/O board	EXT 2U5C 2 x USB (1 x 12V Powered, 1 x 24V Powered USB) 5 x Serial(1 x DB9, with RI/12V/5V Power Output on Pin9, BIOS) 4 x RJ45, Full Signal) EXT 3U4C 3 x USB (2 x 12V Powered, 1 x 24V Powered USB) 4 x Serial (4 x RJ45, Full Signal) 1 x Cash Drawer (RJ12) EXT 4U4C 4 x USB (3 x 12V Powered, 1 x 24V Powered USB) 4 x Serial (4 x RJ45, Full Signal)
Wi-Fi / BT	M.2 for WiFi/BT
Wall Mount Kit	VESA-Compatible, 100 x 100 (mm)
Serial Conversion Cable	RJ-45 to D-sub 9

*Specifications may change without prior notice.

MG BOX I/O Ports



MG BOX Dimensions



CR BOX

CR BOX is an ultra-slim BOX PC with powerful performance applied applied to various fields such as kiosk main system, ATM, digital signage, etc.



CR BOX Features



■ Metal Housing



■ Ultra-slim BOX PC



■ Interface extensibility
(Serial/USB type)



■ UHD resolution
implementation

CR BOX System

	CR BOX
System	
Processors	Intel® Core™ Ultra5 125U 12M Cache, up to 4.3 GHz
Chipset	Intel® Meteor Lake
Memory	4GB Standard, DDR5 5600 MT/s, Socket 2 x SODIMM (Max. 64GB)
Storage	Form factor : SATA 3 (6GB/s) 2.5 inch SSD128GB Mountable : 1 x NVMe M.2 2242 128GB
RAID	Not supported
Audio	HD Audio Codec
Operating Systems	Windows 10 Ver. 21H1 or higher Windows 11 LTSC Ver. 24H2 or higher
TPM	TPM 2.0

CR BOX




Superior performance

CR BOX Interface

	CR BOX
Interface	
Display	3 (2 x HDMI, 1 x USB Type C (Alt-mode))
USB	5 (2 x USB 3.0, 2 x USB 2.0, 1 x USB Type C (Alt-mode))
Serial	1 (COM1, RJ45, with DTR / 12V Power Output on Pin6, Bios) : RS-232 / RS-422 / RS-485, Bios (Default : RS-232) optional
LAN	1 x 1 Gigabit Ethernet (RJ-45, Intel® I219-LM) 1 x 1 Gigabit Ethernet (RJ-45, Realtek RTL8111H)
Audio Port	1 x Line out
SD Card	1 x Micro SD Card Slot (Max. 128GB)
Extension Slot	1 x Mini PCIe for Wireless LAN / BT / LTE
Power	
Power Supply	Adaptor 12V / 5A DIN 3Pin Jack

CR BOX Dimensions




CR BOX Physical & Environmental

	CR BOX
Physical & Environmental	
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
Dimensions (W x D x H)	180 x 183 x 25 (mm), 7.0 x 7.2 x 0.9 (in)
Packing Dimensions (W x D x H)	245 x 240 x 105 (mm), 9.6 x 9.4 x 4.1 (in)
Net Weight	700g, 1.54 lbs
Packing Weight	1,500g, 3.30 lbs
Certification	CE, FCC, KC
Color	Metallic Silver (COVER : Dark Grey)
Options & Peripherals	
Storage	NVMe M.2 128GB
Wi-Fi / BT	M.2 for Wi-Fi/BT
Wall Mount Kit	Supported
Serial Conversion Cable	RJ-45 to D-sub 9

*Specifications may change without prior notice.


CR BOX I/O Ports

FRONT VIEW




REAR VIEW

CR BOX USB



CR BOX Serial



Front view

① LED Indicator (Green/Red)

② Power Button

③ 1 x USB-C

④ 2 x USB 2.0

⑤ 2 x HDMI

⑥ 2 x RJ-45 (Gigabit Ethernet)

⑦ DC-In (12V, 5A)

CR BOX USB

① 1 x Antenna Hole (WiFi / BT/LTE)

② 1 x Audio Line-Out

③ 2 x USB 3.0

④ Com1: 1 x DSUB 9Pin Connector

⑤ 1 x SD Card Slot

⑥ 1 x Antenna Hole (WiFi / BT/LTE)

CR BOX Serial

① 1 x Antenna Hole (WiFi / BT / LTE)

② Com4: 1x RJ-45

③ Com3: 1 x RJ-45

④ Com2: 1 x DSUB 9Pin Connector

⑤ Com1: 1 x DSUB 9Pin Connector

⑥ 1 x Audio Line-Out

⑦ 1 x Antenna Hole (WiFi / BT / LTE)

POSBANK® 99

POSMO

POSMO is a compact touchscreen monitor featuring the same modern and a compact body with a small footprint to save valuable counter space. Industrial-grade LED, LCD panel offers bright and crisp image, extended product life and energy efficiency.



POSMO Features



■ Compact Design



■ Superior Touch Display



■ Better connectivity



■ Flexible installation
(Counter / Wall)

POSMO System

POSMO

Display

	POSMO III-2150	POSMO III-1500
Size	21.5" TFT LCD, LED Backlight	15" TFT LCD, LED Backlight
Resolution	1920 x 1080	1024 x 768
Brightness	300 cd/m ² (typ.)	300cd/m ² (typ.)
Contrast Ratio	1000:1	500:1
View Angle (U/D/R/L)	89°/89°/89°/89°	80°/80°/80°/80° (Typ.)

Touchscreen

Type	Projected Capacitive Touch
Controller Interface	USB Interface

Interface

VGA	1 x VGA
HDMI	1 x HDMI (Factory Option)
USB (A Type)	4 x USB 2.0
USB (B Type)	1 x USB 2.0
MSR	1 x Line out
Audio	2 x 1W (Stereo) (Factory Option)

Power

Power Supply	Adapter 12V, 5A
--------------	-----------------

Physical & Environmental

	POSMO III-2150	POSMO III-1500
Dimensions (W x D x H)	490 x 210 x 337 (mm), 19.3 x 8.2 x 13.3 (in)	364 x 210 x 333 (mm), 14.3 x 8.2 x 13.1 (in)
Net Weight	640 x 300 x 465 (mm), 25.2 x 11.8 x 18.3 (in)	500 x 300 x 470 (mm), 19.6 x 11.8 x 18.5 (in)
Packing Dimensions (W x D x H)	6,200g, 13.7 lbs	4,800g, 10.6 lbs
Packing Weight	9,100g, 20.1 lbs	7,500g, 16.5 lbs
Certification	CE, FCC, KC	CE, FCC, KC

Options and Peripherals

MSR	1 (RJ-45 for MSR, SCR, i-Button)
Multi-Reader	MSR : Comply with ISO 7811, Support 1 & 2 & 3 Track SCR : EMV Level 1 Dallas : i-Button Reader
Wall Mount Kit	VESA-Compatible, 75 x 75 (mm), 100 x 100 (mm)

* Specifications may change without prior notice.

Printers

A printer family provides fast printing speed and high reliability, which makes an ideal POS printer for crowded environment.



Printers Features



| Fast Printing Speed



| Compact Cube Design



| Space Saving



| USB+Serial+Ethernet Interface

Printer System

	POS Printers		
	A400	A6	A8
Print			
Print Method	Direct Thermal		
Print Speed	400mm/s	220 mm/s	250mm/s
Print Resolution	203 dpi (8dots/mm)	203 dpi (8dots/mm)	203.2 dpi (8dots/mm)
Print Width	3inch :79.5 +/- 0.5mm (3.13 +/- 0.02inch) 2inch: 57.5 +/- 0.5mm (2.26 +/- 0.02inch) (Option) 50 +/- 0.5mm (1.96 +/- 0.02inch)	72mm / 48mm	72mm
Print Font			
Character Size	Font A 12 x 24 dots, Font B 9 x 24 dots, Font C 9 x 17 dots	Font A 12 x 24 dots, Font B 9 x 17 dots	Font A 13 x 26 dots, Font B 10 x 20 dots, Extra Font A 12 x 24
Character per Line	Font A 48, Font B 64, Font C 64	Font A 48, Font B 64	Font A 42, Font B 56, Extra Font A 48
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 37 Page International: 32 Unicode , UTF-8	Alphanumeric: 95, Extended Graphics: 128 x 18 Page International: 16	Alpha numeric: 95 Extended Graphics: 128 x 37 Page International: 32 Unicode : UTF-8
Barcode Types	1D : CODABAR, CODE39, CODE93, CODE128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D : PDF417, QR Code	1D : UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE193, CODE128 2D : QR Code, PDF417	1D : Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D : PDF417, QR Code
Graphics	Supporting User-Defined Fonts, Graphics, Logos	Supporting User-Defined Fonts, Graphics, Logos	Supporting User-Defined Fonts, Graphics, Logos
Media			
Type	Thermal Roll Paper		
Paper Feed	Friction Feed		
Loading	Drop in		
Width	80mm, 58mm, 50mm	58mm, 80mm	58mm, 80mm
Roll Diameter	Max. 80mm	Max. 80mm	Max. 83mm
Thickness	70µm	0.06~0.08mm	70µm
Auto Cutter	Partial cut only	Partial Only	Full or Partial Selectable
Partition	2 inch (58mm, 50mm)	2 inch (58mm)	2 inch (58mm) (Option)
Reliability			
MCBF	-	80,000H	60million Lines
TPH	150km	100km	150km
Auto Cutter	1.5million Cuts		

Printer Standard


	POS Printers		
	A400	A6	A8
Standard			
Interface	- USE: 1 x USB 2.0, 1 x Serial(DB9), 1 x Ethernet(10/100M) - USS: 1 x USB 2.0, 2 x Serial(DB9, RJ45)	- A6S : 1 x USB 2.0, 2 x Serial (DB9 + RJ45) - A6E : 1 x USB 2.0, 1 x Serial (DB9), 1 x Ethernet (10/100M)	1 x Serial, 1 x USB 2.0, 1 x Ethernet (10/100M)
Wi-Fi	- WUSS - WUSE: IEEE802.11 b/g/n (2.4GHz only)	-	
Bluetooth	USSB & USEB: V5.2	-	
Support Mobile Operating Systems	Android, iOS (SDK)	Android	Android, iOS (SDK)
Receive Buffer	2MB	4KB	
Printer Driver	Windows Driver, OPOS Driver, Linux CUPS Driver, Virtual COM USB Driver, Utility Program	Windows / OPOS / JPOS / Linux Cups / Mac	Windows Driver, OPOS Driver, Linux CUPS Driver, Virtual COM USB Driver, Utility Program
Utility	NV	Configuration Utility (Config, Interface, NV, Blackmark)	NV
Sensors	Paper End, Cover Open, Paper Near End(Vertical Only)	Paper End, Cover Open, Black Mark	Paper End, Cover Open
Drawer	1 Port		
Power Supply	Adapter 24V, 2.5A (3Pin DIN Plug)	Adapter 24V, 2A (3Pin DIN Plug)	
Temperature & Humidity	Operating : 0 ~ 45°C, 10 ~ 80% RH / Storage : -20 ~ 60°C, 10 ~ 90% RH		
Safety Standards	CE, FCC, KC, J-MIC, CB, UL, PSE	CE, FCC, KC	

Printer Dimensions


	POS Printers		
	A400	A6	A8
Dimensions (W x D x H)	127 x 130 x 127 (mm), 5.00 x 5.11 x 5.00 (in)	130 x 129 x 130.2 (mm), 5.1 x 5.07 x 5.1 (in)	142 x 145 x 195 (mm), 5.6 x 5.7 x 7.7 (in)
Packing Dimensions(W x D x H)	242 x 195 x 162 (mm), 9.52 x 6.68 x 6.38 (in)	242 x 162 x 195 (mm), 9.5 x 6.37 x 7.67 (in)	261 x 290 x 205 (mm), 10.23 x 11.41 x 8.07 (in)
Weight	1,090g, 2.4 lbs	940g, 2.07 lbs.	750g, 1.65 lbs.
Packing Weight	2,020g, 4.45 lbs	1,820g, 4.00 lbs.	2,000g, 4.40 lbs.
Color	Black / White	Dark Grey / White	
Interface Cable	Serial Cable, USB Cable	Serial Cable	WIFI + BT Combo / Serial Cable
Wall Mount Kit	Option(TBD)	Option	Option

* Specifications may change without prior notice.


A6



A8




A400




Printer I/O Ports

A6S




- ① Power supply interface
- ② Interface of cashbox
- ③ Serial interface
- ④ USB interface
- ⑤ RS-232 interface

A8




- ① Drawer Kick-out
- ② Power Connector / 24V
- ③ Serial
- ④ Ethernet
- ⑤ USB (B type)

A400 USE



- ① USB-B(2.0)
- ② Cash Drawer
- ③ Serial(D89)
- ④ DC-IN(24V)
- ⑤ Ethernet (RJ45)

A400 USS



- ① USB-B(2.0)
- ② Cash Drawer
- ③ Serial(D89)
- ④ DC-IN(24V)
- ⑤ Serial (RJ45)


Embedded IoT

POSBANK's Embedded IoT (Internet of Things) Business provides comprehensive system integration, hardware and custom design services. We are closely working with our partners to provide a wide range of IoT applications and perfect solutions for various industries.




Embedded Boards


POSBANK offers a comprehensive range of embedded boards including Mini-ITX mainboards, kiosk and AIO touch computer boards, and SOM-based mainboards with modular CPU and I/O configurations. These boards serve as flexible core platforms for customized IoT, kiosk, and industrial system designs.




Mini ITX Mainboard (Single Layer)



Mini ITX Mainboard (Dual Layer)



KIOSK/AIO Touch Computer Mainboard



SOM based Mainboard (Compact CPU Board + I/O Board)

Embedded Systems

POSBANK's embedded systems, such as MG BOX and CR BOX, are industrial-grade, ready-to-deploy computing platforms built for stable and continuous operation. They provide compact, durable solutions that simplify system integration across kiosk, automation, and smart infrastructure applications.



All-in-One Touch Computer and Frame Computer

All-in-one touch computers and monitors are applicable in smart factories/offices and intelligent warehouses. They are suitable for operating systems for process, scheduling, integrated controls and more. It can be installed and operated in various forms such as stand/wall/panel mounts and ceiling buried types.



OEM-ODM

POSBANK is one of the leading manufacturers of POS and kiosk brands, applying technologically advanced systems to ensure a high level of product quality. With its outstanding development and manufacturing capabilities, POSBANK offers optimized standards by reviewing the various check items required by the customers and projects.




OEM · ODM POS/Kiosk Development & Manufacturing


- Specialization of experienced engineers: Electronic component research, 3D design and rendering, technical design/production, assembly, packaging
- Defined procedures and standards: Organization, adherence to established standards and processes
- Quality Guarantee: Best product quality assurance and follow-up management



POS



KIOSK



BCK

POSBANK provides customized POS and kiosks with optimal specifications and functions required by customers. Prepare for business success with OEM·ODM POS and kiosk solutions suitable for hospitality and retail environments.



POSBANK Global Network



POSBANK HQ

ADDRESS #805-808 New
T-Castle 108,
Gasan digital 2-ro,
Geumcheon-gu,
08506, South Korea

TEL +82-2-2626-9118
FAX +82-2-2626-9119
E-MAIL sales@posbank.com
WEB www.posbank.com



POSBANK USA (California)

ADDRESS 1230 E. 223rd St. Suite
#204, Carson, CA
90745, USA

TEL +1-310-513-1356
FAX +1-310-513-1362
E-MAIL sales@posbank.com
WEB www.posbank.com



POSBANK USA (New York)

ADDRESS 75 Fairchild Ave.
Plainview New York
11803, USA

TEL +1-888-998-1767
ext. 103~104
FAX +1-310-513-1362
E-MAIL sales@posbank.com
WEB www.posbank.com



POSBANK EUROPE

ADDRESS Theodorstrasse 105,
Dusseldorf 40472
Germany

E-MAIL saleseu@posbankeu.com
WEB www.posbank.com



POSBANK, headquartered in Seoul, Korea,
has more than 200 partners in 80 countries
on 6 continents around the world.

We have global locations in North America,
Europe, and Middle East.



POSBANK ITALY

ADDRESS Via Pier Santi
Mattarella,
32, 30030, Gardigiano di
Scorze, Venezia, Italy

TEL +39-41-58-30-594
FAX +39-41-58-30-595
E-MAIL sales@posbank.eu
WEB www.posbank.eu



POSBANK BAHRAIN

ADDRESS Office 11 Building 118A,
Block 707 Road 11, Tubli,
Kingdom of Bahrain

TEL +973-3377-1183
+973-3999-9549
FAX +973-1738-2351
E-MAIL sales@posbank.me
WEB www.posbank.me



POSBANK JAPAN

ADDRESS Yamazaki Building 2F,
2-10-2 Okubo,
Shinjuku-ku, Tokyo
169-0072 Japan

TEL +81-80-7972-4560
E-MAIL sales@posbank.com
WEB www.posbank.com



POSBANK INDIA

ADDRESS 4th Floor. 275 13th
Cross Road, 19th Main
Rd, 4th Sector, HSR
Layout, Bengaluru,
Karnataka 560102
India

TEL +91-80-48900998
+91-94954-85888
E-MAIL sales@posbank.in
WEB www.posbank.in



Copyright © 2026 POSBANK Co., Ltd.

POSBANK and the POSBANK logo are trademarks of POSBANK in the United States and other countries. All trademarks are the property of their respective owners. Intel, Celeron, Core are registered trademarks of Intel Corporation in the United States and other countries. Microsoft, Windows 7, Windows 8.1, Windows 10 IoT Enterprise and POS Ready 7 are registered trademarks of Microsoft Corporation in the United States and other countries. POSBANK shall not be liable for technical or editorial errors or omission contained herein. The information in this publication is informational purposes only and may be altered or amended by POSBANK. All statements regarding POSBANK's direction and intent are subject to change or withdraw without notice. Specifications may change without prior notice.
